

# **CTL CTMS User Configuration**

Aptean Ltd  
Copyright © 2011-2025.

# Contents

1 CTL CTMS User Configuration.....1

# 1 CTL CTMS User Configuration

Users will be set up through CTMS access control for access of CTMS and CTL systems.

The users should be assigned to an access control group - see the standard CTMS functionality guides on this.

Users should have parameters set against them, especially the following:

- The existing BASED\_AT will define the Central Tyre depot to which they have been assigned.
- If the user should have access to all depots, then the ALL\_DEPOTS parameter should be set instead.

CTL users must have access to the CTL menus through their assigned group (typically CTL):

- FIA Reports - CTL-04-REP.CTL-04-REP-02
- Maintenance - CTL.CTL-01-MNT
- Process - CTL.CTL-03-ORD
- Reports - CTL.CTL-04-REP
- Root Menu - CTL.CTL-99-CTL
- Tasks - CTL.CTL-02-TSK
- Tyre Call Logging - CTL-03-ORD.CTL-02-ORD-01
- Vehicle Axle Configuration - CTL-01-MNT.CTL-01-MNT-01
- Vehicle Fleet Maintenance - CTL-02-TSK.CTL-02-TSK-01

Note that these menus should NOT have "In Menu?" ticked.

External (e.g. ITDN) users also require the following parameters:

- A new parameter ?EXTERNAL\_CALL\_LOGGING? will be available. For external users of Call Logging (i.e. ITDN) this parameter should be set.

