

System Parameters List

Aptean Ltd
Copyright © 2011-2025.

Contents

1 System Parameters List.....1

1 System Parameters List

Parameter	Description	
ACC_ACTUAL_DISTANCE	Controls if the distance is rated using actual distance	SYS
ACC_ADD_LINES	Does the user rate by lines and additional tariffs	COS
ACC_ALLOCATE_MANUAL_COST	Allow manual cost payments on orders	SYS
ACC_ALLOW_MULTIPLE_CCY	Can multiple currencies be defined in the database?	SYS
ACC_ALLOW_ZERO_RPE	Allow zero quantity to be returned from get charges (for RPE tier)	SYS
ACC_ALWAYS_APPLY	There are tariffs that should always be applied	SYS
ACC_CALC_SECURITY	Indicates if Security charges are applicable	SYS
ACC_CALC_SERVICES	Service charges applicable	SYS
ACC_CHECK_ORDER	Should order be assessed for rating	SYS
ACC_CONSOL_RADIAL_COSTS	Indicates if radial charges are consolidated at delivery location	SYS
ACC_CONTRACT_OWN	To control if the system looks at the contract or the existing table to identify the charges for own packaging	SYS
ACC_CONTRACT_PICKPACK	To check the relevant contract for a PICKPACK tariff and generate a payment	SYS
ACC_CONTRACT_SERVICES	To control a procedure that will check if there are any service records on the order	SYS
ACC_CUST_FUEL	Apply Customer Fuel Charges	SYS
ACC_Calc_Payment_Ord	Controls whether payment button is displayed on Orders forms - Y or N, Internal Charges are being applied to orders)	SYS
ACC_Calc_Payment_Trip	Controls whether payment button is displayed on Trip forms - Y or N, Trip Cost method is defined against the Carrier Type	SYS
ACC_Calc_Revenue_Ord	Control Order revenue calculation method - CONTRACT or CONTRACT-TPL	SYS
ACC_Calc_Revenue_Trip	Controls whether revenue button is displayed on Trip forms - Y or N, Trip Cost method is defined against the Carrier Type)	SYS
ACC_Calc_Saving_Ord	Controls whether the saving button is displayed on Orders forms - Y or N	SYS
ACC_DEMURRAGE	Number of hours before demurrage charge start	SYS
ACC_EDIT_ORD_CHARGE	Allow users to edit revenue charges	SYS
ACC_FUELSURCH_EVENTDATE	Details whether Fuel Surcharges are calculated based on TENDERED or TRIPSTART date.	SYS
ACC_FUEL_SEC_MODE	Are Fuel and security charges controlled by transport mode	SYS
ACC_INC_ALL_ORDER_COST_PAYMENTS	Include all order cost payments (Y/N)?	COS
ACC_INDEXES	Use Acc indexes	SYS
ACC_INT_CHRG_AT_TRUNK_LEG	Indicates if Internal Charges (trunk and radial) are generated by the trunk leg	SYS
ACC_INVOICE_LOGO	Invoice Logo	COS
ACC_KNOWN_ZONE	Can rating Zone be predicted?	SYS
ACC_LINES_OR_HEADER	Rate orders by line level only (Y), or by header level only or both levels (N)	CUS
ACC_OF_VERSION	Controls format of extract to OF	SYS
ACC_ORD_STD_COST	Control Order standard cost calculation method - CONTRACT or CONTRACT-TPL	COS
ACC_PACKAGES	Are DU type charges separately	SYS
ACC_PLAN_COSTS	Allows user to calc costs from Planned trips	COS
ACC_PROTECT_STATUS	Indicates if Payment status are protected from update to F	SYS



Parameter	Description	
ACC_RATE_BY_PARTY	To control if the rating process will look for a party contract when rating	SYSS
ACC_ROUND_AVG_DU_WEIGHT	Round Avg Du Weight to 3 decimal places for rating	COSS
ACC_SCREENING_CHARGES	Are screening charges applied	SYSS
ACC_SERVICE_METHODS	Controls is services are allocated by methods	COSS
ACC_SHOW_PROFIT	Controls the display of the Profit Field	COSS
ACC_SUPPRESS_RATING	Should rating be prevented when validating orders	CUS
ACC_TRANSPORT_MODE	Is transport mode included in Contract charges	SYSS
ACC_USE_ORD_TRLR_TYPE	Should order revenue be calculated from the order trailer type even when scheduled	COSS
ACC_ZERO_DESPATCHED	Controls if Zero despatched lines are ignored from rating	COSS
ACTIVE_ROLE_DISPLAY	Indicates if the active role is displayed in the tool bar	SYSS
ADDITIONAL_ORDER_VALIDATION	Additional order validation required for product weight	COSS
ADD_CSV_COL_FORMATTING	Add Column Formatting to CSV extracts	SYSS
ADM_EXCLUDE_AUDIT_LOG	Processes that will be excluded from writing audit log records.	SYSS
ADM_EXCLUDE_PACKAGE_MSG	Packages whose adm log messages are not to be written	SYSS
ADM_LOG_ARC_DEL_DAYS	Number of days that ADM_LOG_ARCHIVE messages should be kept for	SYSS
ADM_NO_DISPLAY_MENU	Enable the user to access the menu item	SYSS
ADM_UNKOWN_ORDERS	Identify amended/duplicate orders	SYSS
ADM_UPSHIFT_DU_TYPE	Upshifts the despatch unit type when Y.	SYSS
ADM_UPSHIFT_PRODUCT_TYPE	Upshifts the product type when Y	SYSS
ADM_WRITE_ERRORS	Store fatal form errors in FORM_ERROR_LOG	SYSS
ADR_REGS	Are ADR regulations displayed for trips	COSS
ALLOC_RESOURCE	Are drivers and tractors allocated to own fleet carriers?	SYSS
ALLOC_TRIP_PMNTS	Allocate the trip payments as order costs	SYSS
ALLOW_DIRECT_BAY_MOVES	Should orders be moved directly from the receipt bay or to the despatch bay from the grid?	SYSS
ALLOW_DUPLICATE_CUST_REF	Allow orders with duplicate cust refs but different to locations.	SYSS
ALLOW_ETA_UPDATES	Determines whether the user can update ETA values	COSS
ALLOW_HOLD_ORDERS	allow orders to be place don hold	SYSS
ALLOW_MANUAL_RPE	Allow RPE to be entered (via the inbound EDI) and do not overwrite.	SYSS
ALLOW_MISSING_DEL	Is unit weight sent in the items	SYSS
ALLOW_MULTIPLE_ADD_REFS	Allow multiple additional references for an order values will be (Y/N)	COSS
ALLOW_POC_EDIT	Allow users to edit the POC Flag in Debrief	SYSS
ALLOW_TENDERED_PARAGON_TRIPS	Allow Tendered Trips in Paragon	COSS
ALLOW_TENDERED_PARAGON_TRIPS	Allow Tendered Trips in Paragon	COSS
ALLOW_TRP_DEL_TYPE_UPDATE	Allow Delivery type updates in the planning screen	CAR
ALLOW_UNLOAD_ASSET	Controls if asset records are created as part of unload	SYSS
ALLOW_UNCHEDULE_SCHED_COLL	Controls if menu item Unschedule sched coll is displayed	SYSS
ALTERNATE_DB_NAME	Alternate DB Name	SYSS
ALTERNATE_ORDER_ENTRY	Validate item identifier field	COSS
AMAZON_OWNER_CODE	Asset owner code to pass to Amazon	SYSS
API_CARRIER	Carrier ID for API	SYSS
API_EVENTS	Are events sent out via API	SYSS
API_TEXT_AUTHORISATION	authorisation code for API text	SYSS
API_TEXT_END	Time of day the system stops sending texts	SYSS



Parameter	Description	
API_TEXT_ENDPOINT_URL	URL endpoint for API text	SYS
API_TEXT_START	Time of day the system can start sending texts	SYS
API_WS_ADDRESS	WebService endpoint for API events	SYS
API_WS_ELUCID_ADDRESS	WebService endpoint for API events for Elucid	SYS
API_WS_ELUCID_PASSWD	WebService password for API events for Elucid	SYS
API_WS_ELUCID_USER	WebService username for API events for Elucid	SYS
APPLY_ADDITIONAL_LOC_CHECKS	To enable additional validation checks for location entry.	SYS
ARDO_INBOUND_ARCH	Path for processed XML files that have successfully completed processing, see: int_po_inbound_header (Unilever)	SYS
ARDO_INBOUND_FAIL	Path for processed XML files that have failed processing for reasons described against int_po_inbound_header (Unilever)	SYS
ARDO_INBOUND_PATH	Path for yet to be processed XML files (Ardo)	SYS
ASSEMBLY_DU_TYPE	Assembly DU Type	CO
ASSET_AT_FIXED_ORIGIN	Asset At Fixed Origin	CO
ASSET_DEBRIEF	Indicates if assets debriefed with Items	CO
ASSET_FORMAT	Indicates which order item field will identify an asset	CO
AUTO_COMMIT_EMPTY_STOPS	Commit After Deletion of Empty Stops	CO
AUTO_PLAN_ORDERS	Auto Plan orders onto an existing trip	CO
AUTO_ROUTE_NEW_ORDERS	Automatically plan orders loaded	SYS
AUTO_SCHEDULING	Auto Scheduling of orders	CO
AUTO_SCHED_INACTIVE_DEPOTS	List the inactive depots to exclude from the fixed drop scheduling engine.	SYS
AUTO_SET_DELIVERY_TYPES	Automatically set delivery type rules	CO
BEIG2_FTP_DESTINATION_DIRECTORY	Directory for FTP of BirdsEye Files	SYS
BEIG2_FTP_DESTINATION_IP_ADDRESS	IP for FTP of BirdsEye Files	SYS
BEIG2_FTP_DESTINATION_PASSWORD	Password for FTP of BirdsEye Files	SYS
BEIG2_FTP_DESTINATION_PORT	Port for FTP of BirdsEye Files	SYS
BEIG2_FTP_DESTINATION_USERNAME	Username for FTP of BirdsEye Files	SYS
BEIG2_INBOUND_ARCH	Path for processed XML files that have successfully completed processing, see: int_po_inbound_header	SYS
BEIG2_INBOUND_FAIL	Path for processed XML files that have failed processing for reasons described against int_po_inbound_header	SYS
BEIG2_INBOUND_PATH	Path for yet to be processed XML files	SYS
BEIG2_OUTBOUND_ARCH	Path for processed XML files that have successfully completed processing, see: int_po_inbound_header	SYS
BEIG2_OUTBOUND_FAIL	Path for processed XML files that have failed processing for reasons described against int_po_inbound_header	SYS
BEIG2_OUTBOUND_PATH	Path for yet to be processed XML files	SYS
BEIG_ENABLED	To enable the inbound and outbound file processing on this DB	SYS
BEIG_FTP_DESTINATION_DIRECTORY	Directory for FTP of BirdsEye Files	SYS
BEIG_FTP_DESTINATION_IP_ADDRESS	IP for FTP of BirdsEye Files	SYS
BEIG_FTP_DESTINATION_PASSWORD	Password for FTP of BirdsEye Files	SYS
BEIG_FTP_DESTINATION_PORT	Port for FTP of BirdsEye Files	SYS
BEIG_FTP_DESTINATION_USERNAME	Username for FTP of BirdsEye Files	SYS
BEIG_INBOUND_ARCH	Path for processed XML files that have successfully completed processing, see: int_po_inbound_header	SYS
BEIG_INBOUND_FAIL	Path for processed XML files that have failed processing for reasons described against int_po_inbound_header	SYS
BEIG_INBOUND_PATH	Path for yet to be processed XML files	SYS



Parameter	Description	
BEIG_OUTBOUND_ARCH	Path for processed XML files that have successfully completed processing, see: int_po_inbound_header	SYS
BEIG_OUTBOUND_FAIL	Path for processed XML files that have failed processing for reasons described against int_po_inbound_header	SYS
BEIG_OUTBOUND_PATH	Path for yet to be processed XML files	SYS
BGW_AUTO_REBOOK	Indicates if auto rebook is switched on when non conformance is added	CO
BGW_DUMMY_WASTE	Defines Dummy waste location for BGW.	CO
BGW_TRAILER_SET	Defines which Trailer Types are allowed.	CO
BKG_APPEND_TO_ORDERS	Controls whether Bookings can append to an existing Order if the Slot is already used.	SYS
BKG_AUTO_CREATE_SLOT	Creates slots if no slot exists	SYS
BKG_DEF_COST	Default Cost Centre for Bookings	SYS
BKG_DEF_CUST	Default Customer for Bookings	SYS
BKG_DEF_DELIVERY_DEL_TYPE	Any order that are created via the interface, that are delivering to their final loc	SYS
BKG_DEF_POPULATE_DEL	Any order that are created via bookings will have Del Type populated by system, specific to DSG	SYS
BKG_DEF_TRUNK_DEL_TYPE	Defines the default booking trunk delivery type for any orders being delivered into a x-dock location, default to null	SYS
BKG_GEN_TI_METHOD	Defines whether Gen TI does standard, xdock or both processes, STANDARD, BOTH or XDCK.	SYS
BKG_INCREMENT	Increment exiting Bookings on import rather than overwriting	SYS
BKG_REV_TI_DISBAND_INV_FIX RTE	Should Reverse TIs disband Fixed Trips - Y or N	SYS
BKG_SLOT_INACTIVATE	Controls whether existing Slots are updated to INACTIVE during a Slot Import.	SYS
BKG_TYPE_9_DU_TYPE	Default DU Type for Type 9 Orders	SYS
BKG_USE_BOOKING_STATUS	Defines whether booking status is being used, N, PROVISIONAL, PLANNED or CONFIRMED.	SYS
BMW_DOT_CODE	Tyre Age for BMW	SYS
BUF_OLD_ORD_CLEAR_DAYS	Number of days in the past to be checked by the Buffalo order clear down	SYS
BWSC_GEO_ADD_NETWORK_LOV_LIMIT	When set to Y the LOV for adding network locations will only show SSS, BRANCH and PLANT locations	SYS
CALCULATE_CONTRACTUAL_WEIGHT_TRG	Allow contractual weights to be re-calculated via database trigger (set to N for LFS testing)	SYS
CALC_DIMEN	Calculate volume from dimensions	CO
CALIDUS_ASSIST_BASE_URL	URL for Calidus Assist Install	SYS
CALIDUS_ASSIST_RELEASE_DB	The final part of the URL used to view the release notes, for this database, on Calidus assist.	SYS
CALL_LOGGING_DATE_RANGE	Call Logging Date Range Days	SYS
CAL_DEFAULT_TIME_OFFSET	Default time offset which gets added to times in Order tracking, for users viewing data in different timezone	SYS
CAL_DEFAULT_TIME_ZONE	Description of timezone, used in Order Tracking form, freetext	SYS
CAL_WORKING_DAY_MAP	Defines which days of the week are being worked - Sunday to Saturday, Y or N.	CO
CANCEL_STATUS_CHK	Only orders on Planned trips can be cancelled	SYS
CARGOWISE_BILLING_BRANCH_CODE	Billing Branch Code for Cargowise	CO
CARGOWISE_BRANCH	Branch for Cargowise	CO
CARGOWISE_CONSIGNEE	Consignee name for Cargowise	CO
CARGOWISE_DATABASE	Controls which cargowise database invoices are exported to	CO
CARGOWISE_DEPARTMENT	Department code	CO



Parameter	Description	
CARGOWISE_DESTINATION_PORT	Destination Port	COS
CARGOWISE_EXPORT	Payments are exported to Cargowise	COS
CARGOWISE_ORIGIN_PORT	Origin Port for Cargowise	COS
CARRIER_API_CLIENT_CODE	Value sent across to LFE in API	SYS
CARRIER_API_MANIFEST_READY_TIME	The cut-off time for the ready time for the carrier manifest (HH24:MI).	SYS
CARRIER_API_WS	Endpoint for LFE API	SYS
CARRIER_API_WS_AMEND	Endpoint for Carrier API updates	SYS
CARRIER_API_WS_CANCEL	Endpoint for Carrier API cancellations	SYS
CARRIER_INVOICE_TYPE	Carrier Invoice type	SYS
CARRIER_RULES_ALL	Controls if all du types and products are checked	SYS
CARRIER_WORK_REP_FOOTER_1	The footing printed at the bottom of the CARRIER_WORK_CONF report (first part).	SYS
CARRIER_WORK_REP_FOOTER_2	The footing printed at the bottom of the CARRIER_WORK_CONF report (second part).	SYS
CARR_GAZ_POSTCODE_FORMAT	For which carrier gazetteer formats will the postcode in the file exclude spaces. (List delimited with semi-colons)	SYS
CARR_SRVCE_LEVEL_OFFSET_DAYS	The default minimum number of offset days to calculate the collection job date for UKMail.	COS
CC_FORMAT_PATTERN	Click and Collect Ext Ref format	SYS
CD_DIR	Directory used for copying zipped files	SYS
CFX_CARRIER	Stores the name of CFX Carrier	CAR
CFX_CONTROL	Is there control over which trips go to CFX	SYS
CFX_CONTROL_CUSTOMER	Controls which customers are configured for CFX	CUS
CFX_EXT_LOCATION_NAME	Include the extra location name in the CFX messages (Y/N)	SYS
CFX_LINES_AND_ITEMS	Are items and lines included in CFX file, S,D,B,N	SYS
CFX_NEW_ORDERS	Does adding orders to a trip re-trigger the CFX file?	SYS
CFX_ORDER_ADDRESSES	Are order addresses include in the CFX file	SYS
CFX_ORDER_HEADER	Are orders included in CFX file	SYS
CFX_ORDER_HEADER_TMS	Is the order header TMS section included in CFX file	SYS
CFX_OWNING_DEPOT	Is the owning depot included in the filename?	SYS
CFX_SEND	Are trips sent to CFX	SYS
CFX_STATUS_CHECK	Are carriers checked at status change for CFX?	SYS
CHANGE_DEBRIEF_LABELS	Controls the labels for certain items in the debrief and orders screen	SYS
CHANGE_PRINTER	Is change printer displayed	COS
CHECK_ELUCID_IMBALANCE	Check for stock imbalance at Elucid	COS
CHECK_RESOURCES	Check Resource on existing trips before allocation	SYS
CHG_SCHED_DATE_TRIP	A comma-separated list of trip status for which the schedule may be changed	SYS
CIM_CONF_INBOUND_IDENTIFIER	Pattern for MIC Order Inbound XML	SYS
CIM_CONF_INBOUND_LISTING_NAME	Filename for list of files in directory for MIC XML Order Inbound	SYS
CIM_CONF_LISTING_SCRIPT_NAME	Script name for MIC XML Order Inbound	SYS
CIM_ENABLED	XML Isotrak enabled for this database	SYS
CIM_INBOUND_ARCH	Path for CIM XML archiving	SYS
CIM_INBOUND_FAIL	Path for CIM XML failures	SYS
CIM_INBOUND_IDENTIFIER	Pattern for MIC Order Inbound XML	SYS
CIM_INBOUND_LISTING_NAME	Filename for list of files in directory for MIC XML Order Inbound	SYS
CIM_INBOUND_MAR_IDENTIFIER	Pattern for CIM Order update XML	SYS
CIM_INBOUND_PATH	Path for yet to be processed XML files from CIM	SYS
CIM_LISTING_SCRIPT_NAME	Script name for MIC XML Order Inbound	SYS



Parameter	Description	
CIM_OUTBOUND_ARCH	Path for archiving outbound CIM XML interfaces	SYS
CIM_OUTBOUND_FAIL	Path for failing outbound CIM XML interfaces	SYS
CIM_OUTBOUND_PATH	Path for outbound CIM XML interfaces	SYS
CLICK_CUST	Click and Collect Customer	SYS
CLIENT_CODE_CHECK	Client code assessment for Location import	SYS
CMD_MERGE_DOCUMENTS	The command to merge documents can be stored with any paths that need to be unset to allow the process to be performed.	SYS
CMR_NOTE	Name of the CMR note report	CO
CMR_NOTE1	Name of the CMR note report	CO
CNT_SERVICE_LEVEL_OFFSETS	Enable collection and delivery offsets for service levels (Y/N)	SYS
CNT_SUMMER	Date Summer starts this current year	SYS
CNT_WINTER	Date WINTER starts this current year	SYS
CO2_EMISSIONS_LTR	Defines Amount of CO2 emissions per litre of fuel.	CO
COMBINED_DOCUMENTS_REPORT	Name of the Combined Documents report.	CO
CONSOLIDATE_TRIPS	Remove Duplicate lines when trip is ACCEPTED	SYS
CONSOL_BY_SHIPMENT	Consolidation at Shipment level	CO
CONSOL_RUNNING	Indicates whether the order consolidation process is currently running.	SYS
CONTINGENCY_IMPORT	Contingency Import setting	CO
CON_MAX_RPE	Max RPE per shipment	CO
COST_CENTRE_LOGO	Customer logo filename	CO
COST_CENTRE_POST_MATRIX	Does this cost centre use Post Matrix type charging?	CO
COST_CENTRE_SEGREGATION	Segregate data by cost centre	SYS
CREATE_ORD_MANF	Controls if an order manifest record is created	CO
CSB_EXPORT_PATH	Directory where carrier self billing exports are stored.	SYS
CSB_REPORT_PATH	Directory where carrier self billing reports are stored.	SYS
CS_CLOSE_BY	Display trips in cust serv that are within x miles of order	SYS
CS_DEFAULT_BOOKING_STATUS_OLD	Customer Services Default Booking Status	SYS
CS_DEFAULT_ORDER_STATUS_OLD	Customer Services Default Order Status	SYS
CTMS_CITD_FTP_DESTINATION_DIRECTORY	CITD Destination Directory	SYS
CTMS_CITD_FTP_DESTINATION_IP_ADDRESS	CITD Destination IP Address	SYS
CTMS_CITD_FTP_DESTINATION_PASSWORD	CITD Destination Directory Password	SYS
CTMS_CITD_FTP_DESTINATION_PORT	CITD Destination Directory Port	SYS
CTMS_CITD_FTP_DESTINATION_USERNAME	CITD Destination Directory username	SYS
CTMS_ESI_FTP_DESTINATION_DIRECTORY	Directory for FTP of Outbound Trips Files.	SYS
CTMS_ESI_FTP_DESTINATION_IP_ADDRESS	IP Address for FTP of Outbound Trips Files.	SYS
CTMS_ESI_FTP_DESTINATION_PASSWORD	Password for FTP of Outbound Trips Files.	SYS
CTMS_ESI_FTP_DESTINATION_PORT	Port for FTP of Outbound Trips Files.	SYS
CTMS_ESI_FTP_DESTINATION_USERNAME	Username for FTP of Outbound Trips Files.	SYS
CTMS_MANF_FTP_DESTINATION_DIRECTORY	Manifest Destination Directory	SYS
CTMS_MANF_FTP_DESTINATION_IP_ADDRESS	Manifest Destination IP Address	SYS
CTMS_MANF_FTP_DESTINATION_PASSWORD	Manifest Destination Directory Password	SYS
CTMS_MANF_FTP_DESTINATION_PORT	Manifest Destination Directory Port	SYS
CTMS_MANF_FTP_DESTINATION_USERNAME	Manifest Destination Directory username	SYS
CTMS_OUTBOUND_TRIP_ARCH	File path for Outbound Trips.	SYS
CTMS_OUTBOUND_TRIP_ARCH_TEST	File path for Outbound Trips archive.	SYS
CTMS_OUTBOUND_TRIP_FILENAME	Filename for Outbound Trips.	SYS
CTMS_OUTBOUND_TRIP_FLAG	Flag to permit the creation of Outbound Trips (Y/N).	SYS
CTMS_OUTBOUND_TRIP_MSG_TYPE	The Message Type of the Outbound Trips (Y/N).	SYS
CTMS_OUTBOUND_TRIP_OWNING_DEPOT	The owning depot of the Outbound Trips (Y/N).	SYS
CTMS_OUTBOUND_TRIP_PATH	File path for Outbound Trips.	SYS



Parameter	Description	
CTM_ACCEPT_TRIP_UPDATE_DATA	Should Trip data be entered when user Accepts a trip - Y or N	CAR
CTM_ACCEPT_TRIP_UPDATE_DATA	Should Trip data be entered when user Accepts a trip - Y or N	CAR
CTM_DISP_SCHEDTRIP_OR_BOL	Display Sched/Trip or BOL in Carrier Trip Management - SCHEDTRIP or BOL	CAR
CTM_MSG_CHASE_AFTER	Time(mins) after which a message should be sent to a carrier after failure to respond	CAR
CTM_MSG_CHASE_AFTER	Time(mins) after which a message should be sent to a carrier after failure to respond	CAR
CTM_REFRESH_TIMER_INTERVAL	Automatic Timer Refresh Interval for Carrier Trip Management - Enter value in mins	CAR
CTM_SHOW_TRIP_TIMES	Show trip times in Carrier Trip Management form - Value is Y or N	CAR
CUSTOMER_CONTROLLED_ORDER_REVENUE_ACTUALS	Y/N- greater of planned and actual quantity	SYS
CUSTOMER_LOGO	Customer logo filename	CUS
CUSTOMER_SERVICE_LEVEL	Enable Customer Specific Service Levels	SYS
CUST_DU_CONS_SCHED	Consolidate DU By Schedule	CUS
CUST_UPDATE_ORDER_LINES	Update Orders	CUS
DEBRIEF_DRIVERS_HOURS	Enter Drivers hours worked at debrief	CO
DEBUG	Debug enabled ? - Y or N	SYS
DEFAULT_DEL_TYPE	Default Delivery Type	CO
DEFAULT_DU_TYPE	Default Du Type for NHS	SYS
DEFAULT_ORACLE_DIRECTORY	Stores System directory for TMP_DIR in EXPORT production	SYS
DEFAULT_PART_NO	Default part Number	CUS
DEFAULT_PAR_DEL_TYPE	Default Del type for paragon	CO
DEFAULT_PROD_TYPE	Default Product Type	CO
DEFAULT_REBOOK_DEL_TYPE	Default Del type for Rebook	CO
DEFAULT_SLOT_DELETION_DAYS	Number of days after which an inactive slot is deleted	SYS
DEFAULT_TRAILER_TYPE	Default Trailer Type	CO
DEFAULT_UNSCHEDULED_CARRIER	Indicates a default carrier may be used to print labels for unscheduled orders during packing.	SYS
DEF_AQ_SCHEMA	Schema for use when starting advanced queues	SYS
DEF_CALLOUT_DEL_TYPE	Default Callout Delivery Type	SYS
DEF_COST	Default Cost Centre for NHSBT	SYS
DEF_INSPECT_DEL_TYPE	Default Inspection Delivery Type	SYS
DEF_INSPECT_SERVICE	Default Inspection Service Level	SYS
DEF_SERVICE_LEVEL	Default service level for orders when null	CO
DELCONF_FTP_DESTINATION_DIRECTORY	Directory for FTP of Microlise Files	SYS
DELCONF_FTP_DESTINATION_IP_ADDRESS	IP for FTP of Microlise Files	SYS
DELCONF_FTP_DESTINATION_PASSWORD	Password for FTP of Microlise Files	SYS
DELCONF_FTP_DESTINATION_PORT	Port for FTP of Microlise Files	SYS
DELCONF_FTP_DESTINATION_USERNAME	Username for FTP of Microlise Files	SYS
DELETE_ALL_PMTS_AT_PLANNED	Delete All payments for a trip at Planned Status	CO
DELIVERY_CUTOFF	Cost Centre Delivery Cut Off	CO
DELIVERY_NOTE	Name of the delivery note report	CO
DEL_LEVEL_PARAM	Level of data reported in the Delivery docs	CO
DEL_TIME_OFFSET	The earliest delivery time ahead of the requested delivery date and time sent from PULSE	CO
DESPATCH_EMAIL	Create Despatch email control record	SYS
DESPATCH_REPORT	Name of the despatch note report printed from the trip tree	CO
DHL_INV_EMAIL	List of emails (sep with ;) for monthly DHL Invoicing data	SYS



Parameter	Description	
DIM_CHARGE_WEIGHT	Kg Value for dimensional weight calculation	CUS
DIRECT_CARRIER	Stores the carrier ID that will go direct and not via a location - the via routing code will not be displayed.	SYS
DISABLE_ITEM_ID	Disable the item identifier in order entry	CO
DISPLAY_DESPATCHED_RPE	Display the Actual Despatched RPE Quantity in the Order Detail and Trip Debrief screens?	CO
DISPLAY_PARAGON_LOC_ID	Display Paragon ID and EXT Ref in Locations Screen	SYS
DISPLAY_PO_REF_REPORT	PO Ref to be displayed in delivery note	CUS
DISPLAY_WIC_CODE	Determines if the delivery type of the order for the customer contains a WIC Code and whether the title will be displayed in the Order Details screen	CUS
DISTRIBUTION_OFF	Is revenue distributed as part of trip charges?	SYS
DOM_DIMS	Domestic version of dimensions functionality	CO
DONT_SEND_PLANNED_TO_WEBFLEET	When the parameter is set control record is not sent for PLANNED status	CO
DSG_ALLOW_BKG_IN_PAST	Allow Bookings in the past from the Dixons Bookings interface - Y or N.	SYS
DSG_DEF_DU_TYPE	Default DU Type for Orders created via the Dixons Bookings interface.	SYS
DSG_DEF_PRD_TYPE	Default Product Type for Orders created via the Dixons Bookings interface.	SYS
DSG_TRIP_DTL_PATH	File path for DSG Trip detail messages.	SYS
DU_PARAMS	DUs may be used as charge parameters	SYS
EARLY_ARR_REASON_CODE	Early reason code for trip deliveries	SYS
EDI1214_DELIMITER	File delimiter in EDI1214 file	SYS
EDI1214_ENDOFLINE	File end of line delimiter in EDI1214 file	SYS
EDI1214_SYSTEM	T for test P for Prod	SYS
EDI_CN_ENTITY_CODE	Consignment Entity code for Invoice XML	SYS
EDI_INVOICE_MSG_TYPE	Invoice Message type for Invoice XML	SYS
EDI_MESSAGE_VERSION	Message Version for Invoice XML	SYS
EDI_SH_ENTITY_CODE	Shipment Entity code for Invoice XML	SYS
EDI_STRUCTURE_VERSION	Structure version for Invoice XML	SYS
EFX_CANC_ARCH	Archive folder for EFX cancellation requests	SYS
EFX_CANC_FTP_DESTINATION_DIRECTORY	Directory for FTP of Microlise Files	SYS
EFX_CANC_FTP_DESTINATION_IP_ADDRESS	IP for FTP of Microlise Files	SYS
EFX_CANC_FTP_DESTINATION_PASSWORD	Password for FTP of Microlise Files	SYS
EFX_CANC_FTP_DESTINATION_PORT	Port for FTP of Microlise Files	SYS
EFX_CANC_FTP_DESTINATION_USERNAME	Username for FTP of Microlise Files	SYS
EFX_DEADLINE_HOURS	EFX Default Deadline Hours	SYS
EFX_DEFAULT_CARRIER	EFX Default Carrier	SYS
EFX_DEF_WEIGHT	Default EFX weight per RPE, used in calculation of trip weight for EFX export	SYS
EFX_EXCLUDE_CARR_TYPE_DEB	EFX Exclude Carrier Type from Debrief Messages	CO
EFX_EXT_LOCATION_NAME	Include the extra location name in the EFX messages (Y/N)	SYS
EFX_FAILURE_PATH	File path for failed EFX filed	SYS
EFX_FORMAT	EFX Format	SYS
EFX_FTP_DESTINATION_DIRECTORY	Directory for FTP of Microlise Files	SYS
EFX_FTP_DESTINATION_IP_ADDRESS	IP for FTP of Microlise Files	SYS
EFX_FTP_DESTINATION_PASSWORD	Password for FTP of Microlise Files	SYS
EFX_FTP_DESTINATION_PORT	Port for FTP of Microlise Files	SYS
EFX_FTP_DESTINATION_USERNAME	Username for FTP of Microlise Files	SYS
EFX_IDENTIFIER	EFX file identifier	SYS
EFX_INBOUND_LISTING_NAME	Filename for list of files in directory for EFX XML Trip Inbound	SYS



Parameter	Description	
EFX_INC_TRIP_VEH_TYPE	Include the vehicle type for the trip stop from EFX (Y/N)	COS
EFX_LISTING_SCRIPT_NAME	Script name for EFX XML Inbound	SYS
EFX_PATH	File path for EFX Inbound messages	SYS
EFX_PROCESSED_PATH	File path for processed EFX files	SYS
EFX_SEND_SUB	Send Sub-Contracted Trips to EFX when they go to ACCEPTED status	SYS
EFX_TRIP_ARCH	Archive folder for EFX requests	SYS
EFX_TRIP_DTL_PATH	File path for EFX Trip detail messages.	SYS
EFX_XML_DEB_DELAY	EFX XML Outbound second debrief message delay in minutes	SYS
EFX_XML_DEB_TRIP_STATUS	Determine which trip status generates debrief messages to EFX	COS
EFX_XML_INC_COUNTRYCODE	Will XML messages for EFX include COUNTRYCODE for load and drop locations (Y/N).	COS
EFX_XML_SYSTEM	EFX XML Outbound System Name	COS
EFX_XML_TYPE	EFX Type	COS
EFX_XML_UOM	EFX XML Outbound UOM	COS
ELUCID_API_PROXY	Proxy Sever Elucid	SYS
ELUCID_WS_ADDRESS	Elucid WS Address	SYS
ELUCID_WS_PWD	Elucid WS User	SYS
ELUCID_WS_USER	Elucid WS User	SYS
EMAIL_ACTUALS_FAILURE	Email address for Actuals Failure Email	CUS
EMAIL_CUSTOMER_CARE	Customer Care email address	SYS
EMAIL_CUST_SERVICES_RECIPIENT	The address for the recipient of the emails.	COS
EMAIL_OWN_PACKAGE	Is an e-mail required for an order that contains own packaging (Y/N)?	COS
ENABLE_SEND_BORDERO	Send Bordero Messages	CUS
ENGINE_RUNNING	Indicates whether the Scheduling Engine is running	SYS
EPL_CUST_REF	VPF Test param for 317770	SYS
EPOD_COLLECT_STOCK	To exclude sending a loading stop to EPOD which does not have an order for van stock or to fit new tyres(Y/N)	SYS
EPOD_COMPLETED_UPDATE	Are epod updates sent for COMPLETED trips?	SYS
EPOD_COMPLETE_ON_LOAD_UPDATE	Complete Trip when RTD job sent back from C-ePOD for load updates	COS
EPOD_COMPLETE_ON_RTD	Complete Trip when RTD job sent back from C-ePOD	COS
EPOD_CONCATENATE_JOB_INSTR	Concatenate the special instructions and the order comments for the collection/delivery location as the job instructions (Y/N).	COS
EPOD_CONSOLIDATION_LEVEL	Level of job consolidation for C-ePOD	COS
EPOD_CONTACT_DELIMITER	EPOD contact delimiter	COS
EPOD_CONTAINER_CODE1	What populates this field in EPOD DIMS for dimensions(default) or PARTS for the part numbers if present	COS
EPOD_CONTAINER_CODE2	What populates this field in EPOD DIMS for dimensions or PARTS for the part numbers if present (default)	COS
EPOD_CONTAINER_CODE3	What populates this field in EPOD DIMS for dimensions or PARTS (for the part numbers if present) default NULL	COS
EPOD_CONTAINER_DESCRIPTION	What populates this field in EPOD COMMODITY for the item commodity(default) DESCRIPTION for item desc or PROD_DESC for the prod AKA code and item desc	COS
EPOD_CUSTOMER_INVOICE	Include an EPOD_CUSTOMER_INVOICE section within the EPOD_CUSTOMERS section for the	SYS



Parameter	Description	
	service jobs (Y/N)	
EPOD_CUSTOMER_INVOICE_SXU	To include the EPOD_CUSTOMER section	SYS
EPOD_IGNORE_COL_SIG_DEPOT	Controls if signatures are ignored for cols at depots	COS
EPOD_IGNORE_COL_SIG_DEPOT	Controls if signatures are ignored for cols at depots	SYS
EPOD_ITEM_LEVEL	Send Containers (IC for items or LC for lines) or Products (IP for item or LP for lines) to EPOD	SYS
EPOD_JOB_GROUP_FORMAT	Indicates whether the value passed in the EPL Job Group to EPOD is the Cost Centre (CC), Carried ID (CI), Customer Group (CG) or Customer (CU).	SYS
EPOD_JOB_RETAIN_TIMES	Retain the actual times for the trip stop for the job (Y/N).	COS
EPOD_OWNER_CONFIG	C-ePOD Owner Configuration	COS
EPOD_PREVENT_ASSET_TRACK	Prevents asset tracking through EPOD	COS
EPOD_SEND_CLOSING_TIME	Send Location closing time to C-ePOD	SYS
EPOD_SEND_COD_NAME	Send COD Name to C-ePOD values will be (Y/N)	COS
EPOD_SEND_CONTACT_INFO	Send Contact information to C-ePOD	COS
EPOD_SEND_DRIVER	Is the driver username included? (Y/N)	SYS
EPOD_SEND_EPL_LAT_LONG	Send EPL_LAT and EPL_LONG for job addresses (Y/N)	COS
EPOD_SEND_EQUIPMENT	Controls if equipment requirements are sent to EPOD	SYS
EPOD_SEND_ITEM_AKA_CODE	Send EPL_PRODUCT_CODE with the item AKA code (Y/N)	COS
EPOD_SEND_LOADING_TYPE	Send Loading Type to C-ePOD	COS
EPOD_SEND_RVA_UNIT_TYPE	Send EPL_UNIT_TYPE as the vehicle configuration ID for the services (Y/N)	COS
EPOD_SET_ACTUAL_SIGNATORY_BLANK	Set C-ePOD actual signatory to blank (Y/N)?	SYS
EPOD_SIGNATORY	Controls if signatory is stored from C-ePOD	COS
EPOD_SIGNATURE_STORAGE	Store signature received from C-ePOD	COS
EPOD_SITE_ID_FORMAT	Indicates whether the value passed in the EPL Site ID to C-ePOD is the Database Name(DB), Cost Centre (CC) or Carrier ID (CI).	SYS
EPOD_TNC_STORAGE	Store TNC declaration from C-ePOD	COS
EPOD_UPDATE_ETA	Update Later stops ETA on receipt from C-ePOD	COS
EPOD_VIEW_POD_URL	URL for C-ePOD Documents	SYS
EPOD_WS_ADDRESS	C-ePOD Web Service End Point	SYS
EPOD_WS_ADDRESS_NHSPRD	C-ePOD Web Service End Point	SYS
EPOD_WS_MESSAGE_FORMAT	C-ePOD message format - can either be PARCEL, BULK, RETAIL, MODE1, MODE2 or DELTYPE to define where fields are sent in the web service message	SYS
EPOD_WS_PASSWORD	C-ePOD Web Service Login Password	SYS
EPOD_WS_TIMEOUT	Number of minutes before a WS message will be set to Held	SYS
EPOD_WS_USERNAME	C-ePOD Web Service Login Username	SYS
ETA_LOAD_TIME	Load time in minutes to be used in ETA calculation	SYS
EXE_ARCH_DIRECTORY	Destination directory EXE rcv	SYS
EXE_DESTINATION_DIRECTORY	Destination directory EXE rcv	SYS
EXE_DESTINATION_IP_ADDRESS	Destination for EXE rcv	SYS
EXE_DESTINATION_PASSWORD	Password for EXE rcv	SYS
EXE_DESTINATION_USERNAME	Username for EXE rcv	SYS
EXE_SOURCE_DIRECTORY	Source directory for EXE rcv	SYS
EXTERNAL_CALL_LOGGING	Call Logging External User	SYS
FASTER_SCANNING	Controls if the Planner splits order for planning	SYS
FC_ACCESS_TOKEN	The FleetCheck Access Token, provided by FleetCheck.	SYS
FC_FLEET_KEY	The FleetCheck fleet being updated by C-TMS.	SYS



Parameter	Description	
FC_TIMEOUT	The amount of time to wait when trying to update FleetCheck.	SYS
FC_URL	The base URL for the FleetCheck system.	SYS
FILE_INTERFACE_DIR	File Interface Directory	SYS
FINDTRIP_URL	Find trip webservice URL	SYS
FIT_PRESSURE_HIGH	FIT Report: Pressure Analysis High	SYS
FIT_PRESSURE_LOW	FIT Report: Pressure Analysis Low	SYS
FIT_PRESSURE_VHIGH	FIT Report: Pressure Analysis Very High	SYS
FIT_PRESSURE_VLOW	FIT Report: Pressure Analysis Very Low	SYS
FIT_TREAD_REPLACE_NEXT	FIT Report: RTD in Next Month	SYS
FIT_TREAD_REPLACE_NEXT2	FIT Report: RTD in Next 2 Months	SYS
FIT_TREAD_REPLACE_NOW	FIT Report: RTD in Current Month	SYS
FIXED_IMPORT	Customer is using fixed order import	CUS
FIX_NULL_BOOKING_REF	Set booking Ref to Null for fixed schedules	CO
FLEXIPOD	Set to Y to indicate the Flexipod interface is active	SYS
FLEXIPOD_CARRIERS	Set to Y indicates the Carrier can control if a trip is sent to Flexipod	SYS
FLEXIPOD_CLIENTNUM	Flexipod ClientNum sent in interface	SYS
FLEXIPOD_DEPOTS	Set to Y indicates the Depot can control if a trip is sent to Flexipod	SYS
FLEXIPOD_DROP	Determines the Drop level STOP-OMS or ITEM	SYS
FLEXIPOD_PASSWORD	Flexipod Webservice password	SYS
FLEXIPOD_SCAN_LEVEL	1,2 or 3 to indicate line or item level scanning	SYS
FLEXIPOD_SCAN_TYPE	Contents and items	SYS
FLEXIPOD_SPLIT	Are orders to be split?	SYS
FLEXIPOD_SYSTEM	Flexipod SYSTEM ID sent in interface	SYS
FLEXIPOD_USERCODE	Flexipod Webservice usercode	SYS
FLEXIPOD_USERNAME	Flexipod Webservice username	SYS
FLEXIPOD_WEBSERVICE	Flexipod webservice endpoint URL	SYS
FLEXIPOD_WEBSERVICE_TASK	Flexipod webservice endpoint URL for Tasks	SYS
FLEXIPOD_WEBSERVICE_UI	Flexipod webservice endpoint URL	SYS
FORCE_ITEM_SCAN	Is driver required to scan at debrief?	SYS
FORMS_ALERT_MESSAGE_MODULE	Alert Messages Form	SYS
FORMS_CS_PATH	Forms Client Server Path	SYS
FORMS_DEFAULT_MODULE	Default Module accessed when C-TMS is started - ORI_STATS, ORI_STATS_JRL or ORI_STATS_WATERFALL	SYS
FORMS_DEFAULT_ORDERS_MODULE	Default Orders Form - ORDERS_WIDE, ORDERS or ORD_ENTRY_TARGET	SYS
FORMS_DEFAULT_TRIP_MODULE	Default Trip Form - TRIPSUM or TRIPSUM_JRL	SYS
FORMS_PASSWORD_MODULE	Password Change form.	SYS
FORMS_PATH	Forms Path	SYS
FORMS_WEB_PATH	Determines where on the server forms are being obtained from for this database	SYS
FORMS_WEB_PATH_BLUE	Blue forms	SYS
FTP_SERVER_LOG	Create server logs for FTP send to prove delivery	SYS
FTP_TRANSMIT_TIME_LIMIT	Determines the time limit (in minutes) above which a file being transferred is considered to be failed instead of pending.	SYS
FTP_WRITE_LOC	FTP Write location	SYS
FULL_LOAD_GROUPAGE_FLAG	Controls whether Full load \ Groupage flag is checked when changing Trip status	SYS
FULL_LOAD_THRESHOLD	Maximum weight threshold for any FTL	SYS
GEL_DU	Identifies which du types include GEL	CO
GEO_ASKGEO_PROXY	Proxy server setting for AskGEO web server	SYS



Parameter	Description	
GEO_ASKGEO_TIMEOUT	AskGEO web server time out	SYS
GEO_ASKGEO_URL	AskGEO web server URL	SYS
GEO_DEFAULT_COUNTRY	Default country for new locations	SYS
GEO_DEFAULT_DEPOT	Default depot for new locations	SYS
GEO_DEFAULT_LOAD_RATE	Default Loading Rate for locations.	SYS
GEO_DEFAULT_SESSION_COUNTRY	Default Country Code for locations created from sessions	SYS
GEO_DEFAULT_UNLOAD_RATE	Default Unloading Rate for locations.	SYS
GEO_DRIVE_TIME_DTL_ONLY	Allows TRANSIT DAYS to be overridden by Drive Time in GEO_NET, YES or NO.	SYS
GEO_DT_ADDR_FMT	Determines the format of the Address string passed to external Map application, e.g. MapPoint, for Address Location Matching	SYS
GEO_DT_CALC	Determines the distance and time calculation methods - NET, NETR, LINE, PCMS	SYS
GEO_DT_CALC_ORD	Determines distance calculation method for orders	COS
GEO_DT_CALC_PAR_INT	Override for dist/time method for Paragon Interface	SYS
GEO_DT_DFLT_SPEED	Default truck speed assumed in approximation of driving time.	SYS
GEO_DT_DISTANCE_FACTOR	"Wiggle" factor applied to straight-line distance to approximate Road distance.	SYS
GEO_DT_DISTANCE_UNITS	Current distance unit - miles or kilometres	SYS
GEO_DT_DISTANCE_UNITS	Current distance unit - miles or kilometres	COS
GEO_DT_PCMS_TIMEOUT	Number of seconds to wait for PCMS to calculate distance and time.	SYS
GEO_DT_PCMS_TIMEOUT_ORD	Number of seconds to wait for NAVTEQ for order distance calculation	COS
GEO_HERE_DISTANCE_TYPE	Set to either miles or leave blank	COS
GEO_HIDE_SWAP_LOCATIONS	It is to exclude SWAP locations from list of Location_ID in location maintenance screen	SYS
GEO_KEEP_LATLONG	Keep Lat-Long when entered	SYS
GEO_LOCATION_STACK	Switch on stack specific location fields	SYS
GEO_LOC_ADD1_MAND	Address Line 1 must be entered	SYS
GEO_LOC_CUST_CTRY	Enable a customer to be specified for a location to be maintained for one of multiple countries? (?Y/N)	SYS
GEO_LOC_IMP_POST_PLAN	Populate the postal and planning regions using rules in country and static data when doing location import	SYS
GEO_LOC_PCDE_MAND	Post code must be entered	SYS
GEO_LOC_RADIAL_ROUTES	Indicates if a radial route will be stored for the location based on the fixed route stop for collection/delivery (Y/N).	SYS
GEO_LOC_TOWN_MAND	Town must be entered	SYS
GEO_MAX_INVENTORY	Maximum inventory threshold for warning	SYS
GEO_MIN_INVENTORY	Minimum inventory threshold for warning	SYS
GEO_NAVTEQ AJAX_LOGIN	NAVTEQ Ajax Login	SYS
GEO_NAVTEQ_CITY_SPEED	City Road Speed for NAVTEQ	SYS
GEO_NAVTEQ_COUNTRY_SPEED	Country Road Speed for NAVTEQ	SYS
GEO_NAVTEQ_FAST_SHORT	Fastest or Shortest Method for NAVTEQ Route calculation	SYS
GEO_NAVTEQ_JAVA	NAVTEQ Java	SYS
GEO_NAVTEQ_LOGIN	NAVTEQ Login	SYS
GEO_NAVTEQ_MAP_DIR	NAVTEQ Maps Folder	SYS
GEO_NAVTEQ_MAP_SHOW	NAVTEQ Maps Folder for WEBSHOW	SYS
GEO_NAVTEQ_MOTOR_SPEED	Motorway Speed for NAVTEQ	SYS
GEO_NAVTEQ_PROXY	Proxy Sever for NAVTEQ	SYS
GEO_NAVTEQ_URL_LOC	NAVTEQ Location URL	SYS



Parameter	Description	
GEO_NAVTEQ_URL_MAP	NAVTEQ Map URL	SYS
GEO_NAVTEQ_URL_MAP_ALL	NAVTEQ Map URL	SYS
GEO_NAVTEQ_URL_ROUTE	NAVTEQ Route URL	SYS
GEO_NET_TABLE	Network Table	SYS
GEO_NLP_ALT_PROXY	Proxy Sever for NLP 11g	SYS
GEO_NLP_ALT_URL_LOC	Alternative URL for Geocode service on NLP system	SYS
GEO_NLP_ALT_URL_ROUTE	Alternative URL for Calculate Route service on NLP system	SYS
GEO_NLP_API_KEY	API Key for NLP	SYS
GEO_NLP_APP_LOC	App_ID for Geo Code call to NLP system	SYS
GEO_NLP_APP_MAP	App for Map service on NLP system	SYS
GEO_NLP_APP_ROUTE	App_ID for Route call to NLP system	SYS
GEO_NLP_CAR_TRUCK	Nokia travel time calculations to be based on a truck or a car	SYS
GEO_NLP_DISTRICT_PARAM	Control which field (TOWN/LINE3) is sent as district to Nokia	SYS
GEO_NLP_FORMAT_FREETEXT	NLP Freetext Format	SYS
GEO_NLP_FORMAT_QUALIFIED	NLP Qualified Format	SYS
GEO_NLP_JAVA	Java for NLP to create PDF	SYS
GEO_NLP_JS_MULTI	Location for the show map multiple map printout in JavaScript	SYS
GEO_NLP_LATLONG_ACCURACY	NLP Geocode Accuracy	SYS
GEO_NLP_MAP_DIR	Directory for PDF of maps	SYS
GEO_NLP_MAP_SHOW	Directory for PDF of maps	SYS
GEO_NLP_MOTORWAY	Motorway Preference for NLP distance calculations	COS
GEO_NLP_PROXY	Proxy Sever for NLP	SYS
GEO_NLP_TOKEN_LOC	NLP Geocode Token	SYS
GEO_NLP_TOKEN_MAP	Login token for Map service on NLP system	SYS
GEO_NLP_TOKEN_ROUTE	Login token for Calculate Route service on NLP system	SYS
GEO_NLP_URL_LOC	Nokia Location Platform Geocode URL	SYS
GEO_NLP_URL_MAP	URL for Map service on NLP system	SYS
GEO_NLP_URL_ROUTE	URL for Calculate Route service on NLP system	SYS
GEO_NLP_USE_ALTERNATE	Use Alternative URLs and Proxy	SYS
GEO_POP_PLANNING_REGION	Controls whether the Planning Region is populated from the look up table - Y or N.	SYS
GEO_SLOT_IMPORT_FILE	Name of Slot Import file	SYS
GEO_SLOT_IMPORT_PATH	Slot Import path	SYS
GEO_SUBURB	Town must match a Zone	SYS
GEO_TOMTOM_ACCOUNT	TomTom account	SYS
GEO_TOMTOM_ARCH_DAYS	Number of days to keep the TomTom data before archiving	SYS
GEO_TOMTOM_AUTO_AREA_RADIUS	Radius (m) of temporary TomTom areas	SYS
GEO_TOMTOM_FENCE_CARR	List of carriers to test TomTom Geo-fence breaks	SYS
GEO_TOMTOM_FENCE_VAR	Variation of time in hours from planned for TomTom Geo-fence breaks to update stop	SYS
GEO_TOMTOM_FENCE_VEH	List of vehicles to test TomTom Geo-fence breaks	SYS
GEO_TOMTOM_GETMSGGS_URL	TomTom web service	SYS
GEO_TOMTOM_LATE_MINS	TomTom Late Reason Variance Minutes	SYS
GEO_TOMTOM_LATE_REASON	TomTom Late Reason Code	SYS
GEO_TOMTOM_ORDER_DEBRIEF	List of Delivery types allowing change	CAR
GEO_TOMTOM_PASSWORD	TomTom password	SYS
GEO_TOMTOM_PROXY	Proxy server setting for TomTom web server	SYS
GEO_TOMTOM_SENDORD_URL	TomTom web service to send orders	SYS
GEO_TOMTOM_SEND_CUST_REF	Send order customer ref to TomTom	SYS



Parameter	Description	
GEO_TOMTOM_TIMEOUT	TomTom web server time out	SYS
GEO_TOMTOM_TRIP_COMPLETE	TomTom to automatically complete trips	SYS
GEO_TOMTOM_TRIP_EN-ROUTE	Set trip status to EN-ROUTE from TomTom	SYS
GEO_TOMTOM_USERNAME	TomTom username	SYS
GEO_VALIDATE_LOCATION_NAME	Indicates whether the system should check for duplicate location names (as well as IDs) when creating/updating locations	SYS
GLO_CUSTOMER	Customer for Unilever Gloucester	SYS
GLO_FTP_DESTINATION_DIRECTORY	Directory for FTP of Unilever Files	SYS
GLO_FTP_DESTINATION_IP_ADDRESS	IP for FTP of Unilever Files	SYS
GLO_FTP_DESTINATION_PASSWORD	Password for FTP of Unilever Files	SYS
GLO_FTP_DESTINATION_PORT	Port for FTP of Unilever Files	SYS
GLO_FTP_DESTINATION_USERNAME	Username for FTP of Unilever Files	SYS
GLO_INBOUND_ARCH	Path for processed XML files that have successfully completed processing, see: int_po_inbound_header (Unilever)	SYS
GLO_INBOUND_FAIL	Path for processed XML files that have failed processing for reasons described against int_po_inbound_header (Unilever)	SYS
GLO_INBOUND_PATH	Path for yet to be processed XML files (Unilever)	SYS
GLO_LOCATION	Location for Unilever Gloucester	SYS
GLO_OUTBOUND_ARCH	Path for processed XML files for Unilever	SYS
GLO_OUTBOUND_FAIL	Path for processed XML files for Unilever that have failed processing	SYS
GLO_OUTBOUND_PATH	Path for yet to be processed XML files for Unilever	SYS
HIGHLIGHT_SMS_EMAIL	Highlight order Green if SMS or email notification required	COS
HKP_Clear_Archive_Messages	Age of ARCHIVED messaging records that are to be cleared.	SYS
HKP_Clear_Messages	Age of messaging records that are to be cleared.	SYS
HTTPS_CALL	It is related to switching from HTTP to HTTPS	SYS
HTTPS_PASSWORD	The password for URL commands in the database.	SYS
HTTPS_WALLET_FILE	The wallet file for URL commands in the database.	SYS
HTTP_WALLET_TOMTOM	Location of wallets for TOMTOM https	SYS
ICE_DU	Identifies which du types include ICE	COS
IGGESUND_IDENTIFIER	Identifier for IGGESUND inbound order files	SYS
IGGESUND_LISTING_NAME	List for IGGESUND files	SYS
IGGESUND_LISTING_SCRIPT_NAME	KSH for IGGESUND files	SYS
IMP_BWSC_DEF_CARRIER	Default Carrier for BWSC import for self delivery suppliers	COS
IMP_CARRIER_LANE_COUNTRY_CODE	Country code for each cost centre imported on Carrier_Lane - INDUSTRIAL	COS
IMP_CHANGE_DECIMALS	Correct commas and decimal points for Dimensions	CUS
IMP_COL_DATE_REQD	Collection Date must be specified for imports	COS
IMP_CREATE_ITEM_ID	Controls if Item identifiers are system generated in CSV	CUS
IMP_FULL_LOC_ADDR_MATCH	Check the addresses match for the location name, address line 1, postcode, country and type for imported orders before creating a new location (Y/N).	SYS
IMP_LOC_ID_ONLY	Only validate the location id when importing orders not the address lines	SYS
IMP_OVERRIDE_SOURCE_REF	Set source system and control additional functionality in ORD_LINE_ITM CSV order import	SYS
IMP_RESET_ORD_WINDOWS	Reset Order windows during Import	COS
IMP_RESET_ORD_WINDOWS	Reset Order windows during Import	CUS
IMP_TI_ORDER_CALC_WEIGHTS		COS



Parameter	Description	
	CSV Import - Calculate weights from dims(Y=X*Y*Z/6000)	
IMP_TI_ORDER_CHECK_SMS	CSV Import - Check contact numbers can be used as SMS numbers	COS
IMP_TI_ORDER_DEFAULT_DU	CSV Import - Default DU Type Method	COS
IMP_TI_ORDER_GEN_ITEMS	CSV Import - Generate order items from Qty	COS
IMP_TI_ORDER_GEN_LOC	CSV Import - Location Name generation by Post Code	COS
IMP_TI_ORDER_QTY_ADD	CSV Import - Add line qty	COS
IMP_TI_ORDER_REVENUE_LIMIT	CSV Import -Pre-call above revenue limit (Numeric Limit).0 means no pre-call	COS
IMP_TI_ORD_GEN_LOC_NAME	Send Supplier Collection Messages	CUS
IMP_USE_DEFAULT_DU	Use Default DU Type in import	CUS
IMP_USE_DEFAULT DU	Use Default DU Type in import	CUS
IMP_USE_GERMAN_DECODE	Controls if location names are decoded from German	SYS
INBOUND_ARDO_IDENTIFIER	Identifier for MTS PO Inbound Ardo files	SYS
INBOUND_ARDO_LISTING_NAME	Listing file for Ardo inbound XML files	SYS
INBOUND_ARDO_SCRIPT_NAME	Command file for Ardo inbound XML files	SYS
INBOUND_BEIG2_IDENTIFIER	Identifier for MTS PO Inbound DAI_TMS_BEIG_ORD_YYYYMMDDHHMMSSII.XML	SYS
INBOUND_BEIG2_LISTING_NAME	Listing file for BEIG inbound XML files	SYS
INBOUND_BEIG2_SCRIPT_NAME	Command file for BEIG inbound XML files	SYS
INBOUND_BEIG_IDENTIFIER	Identifier for MTS PO Inbound DAI_TMS_BEIG_ORD_YYYYMMDDHHMMSSII.XML	SYS
INBOUND_BEIG_LISTING_NAME	Listing file for BEIG inbound XML files	SYS
INBOUND_BEIG_SCRIPT_NAME	Command file for BEIG inbound XML files	SYS
INBOUND_FAILURES_PATH	Path for failed inbound files	SYS
INBOUND_GLO_IDENTIFIER	Identifier for MTS PO Inbound Unilever files	SYS
INBOUND_GLO_LISTING_NAME	Listing file for GLO inbound XML files	SYS
INBOUND_GLO_LOA_IDENTIFIER	Identifier for MTS PO Inbound Unilever LOA files	SYS
INBOUND_GLO_SCRIPT_NAME	Command file for GLO inbound XML files	SYS
INBOUND_POM_IDENTIFIER	Identifier for MTS PO Inbound MTS_POMI_<YYYYMMDDHH24MISS>_<10 DIGIT SEQ>.XML	SYS
INBOUND_POM_LISTING_NAME	Listing file for POM inbound XML files	SYS
INBOUND_POM_SCRIPT_NAME	Command file for POM inbound XML files	SYS
INBOUND_PROCESSED_PATH	Path for processed inbound files	SYS
INBOUND_UNI_IDENTIFIER	Identifier for MTS PO Inbound Unilever files	SYS
INBOUND_UNI_LISTING_NAME	Listing file for UNI inbound XML files	SYS
INBOUND_UNI_SCRIPT_NAME	Command file for UNI inbound XML files	SYS
INCLUDE_CDATA_TAG	Use CDATA tag around XML tags values and allowed values will be (Y/N) which will be used to control escaping of special characters like &	SYS
INCLUDE_FAILED_ORDERS	Include Failed Orders as CANCELLED for API	COS
INCL_ROUTE_CODE	Include Baxter Route code and delivery method	COS
INCOMPLETE_ORDERS_WARNING	Display warning message on trip status change if no order items exist	COS
INHERIT_LAT_LONG	Inherit Lat/Long details from parent address	CUS
INNER_OUTER_DU	Inner and outer du types for rating	COS
INTERFACE_FORMAT	Controls the interface format for inbound orders	SYS
INTERFACE_INBOUND_PATH	Path for Inbound files	SYS
INT_ADD_MOD43_CD	Store the Modulo 43 check digit as a suffix for the order item for the barcode label (Y/N).	COS
INT_ADD_MOD43_CD	Store the Modulo 43 check digit as a suffix for the order item for the barcode label (Y/N).	CUS
INT_ALTERNATE_DB	Determines if alternate_db is used as a condition in the INT_MSG code	SYS



Parameter	Description	
INT_CARRIER_DET	Used to control which carrier details cursor is fetched in INT_MSG.PROCESS_TRIP_DTL_MSG	SYS
INT_CHARGES	Determines whether internal charging is based on COST_CENTRE or GROUP_NAME	SYS
INT_DECODE_UNISON	Used to control which DECODE_VALUE is used in INT_MSG	SYS
INT_DROP_POSTCODE	Determines how v_string is built within INT_MSG.PROCESS_EFX_TRIP_DTL_MSG part of INT_MSG alignment	SYS
INT_ERRNUM	Used to establish whether error numbers should be inserted into VALIDATION_ERROR in INT_MSG	SYS
INT_IGNORE_DESP_QTY	Send despatch messages even when despatch quantity is not set	SYS
INT_KEEP_FILE	Do not remove files from delivery folder	SYS
INT_MSG_TYPE	Determines whether a cursor is fetched or a hard coded if IN the INT_MSG.READ_BBOKING_HEADER procedure. Part of Alignment process.	SYS
INT_ORDER_COMMENT	Indicates if the order_comments in INT_MSG.PROCESS_UNSION_FILE is selected as a substring	SYS
INT_ORDER_CORRECT	Indicates if interface files are corrected	SYS
INT_READ_EFX_COMMENTED_OUT	Indicated if code is commented out in EFX procedure of INT_MSG part of alignment	SYS
INT_READ_EFX_CURSOR	Indicates if C_EFX_TRIPS cursor is based on trip or load part of INT_MSG alignment	SYS
INT_REVERSE_DECODE	Indicates if INT_MSG.PROCESS_EXE_OUTBOUND_FILE requires a call to IMP_REVERSE_DECODE in the current database	SYS
INT_TRAILER_TYPE	DECODE or REVERSE to determine how trailer type is extracted in INT_MSG.PROCESS_EFX_TRIP_DTL_MSG	SYS
INT_TRANSHIP_POS	Used to determine TRANSHIP_IND is in the incoming file for INT_MSG.READ_BOOKING_DETAIL	SYS
INT_TRIP_STOP_DATE	Determines which date (LATE DEL or DEPART) is passed to the string in INT_MSG	SYS
INT_UNISON_ERRNUM	Indicates if errnum should be included when inserting data into validation_error field in INT_MSG.PROCESS_UNISON_FILE	SYS
INT_USE_NEW_DB	Determines which procedures within INT_MSG use the new database name	SYS
INT_XML_DAYS_PAST	Used to set how many days into the past the dp_pulse package should look for locked records	SYS
INVOICE_DIR	Directory for storing invoices when printed	SYS
INV_ACT_PMNTS_DAYS	Process payments for a set number of days prior to the period end date or the current date for the next invoice.	SYS
INV_SEARCH_FROM_OFFSET	Controls how many days in the past to default the from search in the INVOICES form.	SYS
INV_SEARCH_TO_OFFSET	Controls how many days in the future to default the from search in the INVOICES form.	SYS
INV_SET_PERIOD	Set the period for the invoice based on the current date (Y/N)	SYS
ISOTRAK_BATCH_JOB_SIZE	Number of job records that are processed each minute via the ISOTRAK interface	SYS
ISO_ENABLED	ISO enabled for this database	SYS
ISO_FTP_DESTINATION_DIRECTORY	Directory for FTP of ISOTRAK Files	SYS
ISO_FTP_DESTINATION_IP_ADDRESS	IP for FTP of ISOTRAK Files	SYS



Parameter	Description	
ISO_FTP_DESTINATION_PASSWORD	Password for FTP of ISOTRAK Files	SYS
ISO_FTP_DESTINATION_PORT	Port for FTP of ISOTRAK Files	SYS
ISO_FTP_DESTINATION_USERNAME	Username for FTP of ISOTRAK Files	SYS
ISO_INBOUND_ARCH	Path for inbound ISO XML archiving	SYS
ISO_INBOUND_FAIL	Path for ISO XML failures	SYS
ISO_INBOUND_IDENTIFIER	Pattern for ISO Trip Inbound XML	SYS
ISO_INBOUND_LISTING_NAME	Filename for list of files in directory for ISO XML Trip Inbound	SYS
ISO_INBOUND_PATH	Path for yet to be processed XML files from ISO	SYS
ISO_LISTING_SCRIPT_NAME	Script name for ISO XML Trip Inbound	SYS
ISO_OUTBOUND_ARCH	Path for archiving outbound ISO XML interfaces	SYS
ISO_OUTBOUND_FAIL	Path for failing outbound ISO XML interfaces	SYS
ISO_OUTBOUND_PATH	Path for outbound ISO XML interfaces	SYS
ISO_Queue_Name	ISOTRAK Queue Name	SYS
ISO_RECON_MODE	Determine whether messages should be deleted or reconciled, then delete or update as appropriate, ARCHIVE or DELETE	SYS
ISO_Sched_Prefix	ISOTRAK Schedule Prefix	SYS
ISO_Signature	ISOTRAK Signature	SYS
JAVAVM_PROFILE	javavm profile	SYS
KCC_DEL_INFO_PATH	File path for KCC Delivery Information Export	SYS
KER_LOADING_FTP_DIRECTORY	Specify the directory for the Kerridge Loading file	CO
KER_LOADING_FTP_FILENAME	Specify the Filename for the Kerridge Loading file	CO
KER_LOADING_FTP_IP_ADDRESS	Specify the IP Address for the Kerridge Loading file	CO
KER_LOADING_FTP_PASSWORD	Specify the Password for the Kerridge Loading file	CO
KER_LOADING_FTP_PATH	Specify the path for the Kerridge Loading file	CO
KER_LOADING_FTP_PORT	Specify the Port for the Kerridge Loading file	CO
KER_LOADING_FTP_USERNAME	Specify the Username for the Kerridge Loading file	CO
KER_WEB_PATH	URL for show web Kerridge Files	CO
LABEL_DIR	Directory for storing the labels when printed	CO
LABEL_FILE	Directory for storing the labels when printed	CO
LABEL_FILE_UNSCHEDULED	The label format for when the order is UNSCHEDULED.	CO
LABEL_FORMAT	Label format for Orders	CO
LABEL_GROUP	Delivery Type for which labels will be printed	CO
LABEL_LOGO_FILE	Set label logo file	SYS
LANE_RATE_CHARGING	lane rates calc	CO
LAST_RELEASE_DATE	Last release for this database. NB. UPDATED_DATE (updated by trigger) stores the real value (see ORI_STATS). Change VALUE after each release.	SYS
LBO_CUTOFF_TIME_DEFAULT	Latest time by which a Lane Based Order must be places if Cut-off functionality is switched on	SYS
LBO_CUTOFF_TIME_ENABLE	LBO Cut-off times enabled - Y or N	SYS
LBO_FUTURE_ORDER_LIMIT_DAYS	Maximum number of days in future that LB Order can be created	SYS
LFE_API_AUTHORISATION	Client Ref for authorisation	SYS
LFE_API_VERSION	11 for 11g, 12 for 12c	SYS
LICENCE_MONITOR_LEVEL	Licence monitor alert level	SYS
LINE_ITEM_TOTALS	Controls if service payments are generated	CO
LOADING_REPORT	NON Cost centre Loading Report	SYS
LOAD_LEVEL_PARAM	Level of data reported in the Load List	CO
LOCATION_DECODE_VALIDATION	Validate Addresses using decode values	CO
LOGINEXT_API_TOKEN	API Token for Loginext	SYS
LOGINEXT_ENDPOINT	Endpoint address for Loginext	SYS
LOGIX_ARCH_DIR	Folder for archive of Logix files	SYS



Parameter	Description	
LOGIX_CREATE_FILE	Create a file containing CLOB	SYS
LOGIX_DEL_PRIORITY_DAYS	Number of days before late delivery when prioritized in Route Optimiser	SYS
LOGIX_DIR	Folder for Logix files	SYS
LOGIX_MASTER_PROFILE	Profile for Logix API webservice	SYS
LOGIX_MASTER_WORK_AREA	LogiX Master Work area directory name	SYS
LOGIX_PASSWORD	Password for Logix API webservice	SYS
LOGIX_PROFILE	Profile for Logix API webservice	SYS
LOGIX_PROJECT	Project for Logix API webservice	SYS
LOGIX_PROXY	Proxy server name for Logix API webservice	SYS
LOGIX_RANGE	Range of schedules to send	SYS
LOGIX_RANGE_OLD	Range of schedules to send	SYS
LOGIX_SCHEDULE_MATRIX	How Many Days in the future to Recalculate Planned Transport?	SYS
LOGIX_SERVER_NAME	LogiX server name	SYS
LOGIX_SLOT_CUTOFF_TIME	Cut-off time for planning trunks in LogiX import	SYS
LOGIX_TIMEOUT	Timeout for Logix API webservice	SYS
LOGIX_URL	URL for Logix API webservice	SYS
LOGIX_USERNAME	Username for Logix API webservice	SYS
LOGNET_INT_DIR	LOGNET file path.	SYS
LOGO_FILE	Logo file	SYS
LOGO_FILE_BW	Logo file in Black and White for system usage (e.g. on labels).	SYS
LOGO_PATH	Site specific location of logo files	SYS
LOTS_ADD_DEBRIEF	LOTS Additional Debrief Details	COS
LOTS_DEL_CUST_SIGNATORY	Controls if DEL messages for LOTS require an actual signatory - Y to hold messages.	COS
LOTS_DEL_MSG_TRIP_STATUS_COMPLETE	Send LOTS DEL Message if trip status set to COMPLETE (Y/N)	COS
LOTS_EXPORT_TYRE	LOTS export tyre	COS
LOTS_FTP_DESTINATION_DIRECTORY	Final Destination directory for FTP of LOTS Files	SYS
LOTS_FTP_DESTINATION_IP_ADDRESS	IP for FTP of LOTS Files	SYS
LOTS_FTP_DESTINATION_PASSWORD	Password for FTP of LOTS Files	SYS
LOTS_FTP_DESTINATION_PORT	Port for FTP of LOTS Files	SYS
LOTS_FTP_DESTINATION_USERNAME	Username for FTP of LOTS Files	SYS
LOTS_FTP_PUT_DIRECTORY	Mid-Send directory for FTP of LOTS Files	SYS
LOTS_INBOUND_ARCH	Path for archiving inbound LOTS XML interfaces	SYS
LOTS_INBOUND_FAIL	Path for failing inbound LOTS XML interfaces	SYS
LOTS_INBOUND_IDENTIFIER	Pattern for LOTS Trip Inbound XML	SYS
LOTS_INBOUND_LISTING_NAME	Filename for list of files in directory for LOTS XML Trip Inbound	SYS
LOTS_INBOUND_PATH	Path for inbound LOTS XML interfaces	SYS
LOTS_INC_ORDER_HEADER_CONFIRM	Includes the ORDER_HEADER_CONFIRM section in the DEL file for LOTS.	SYS
LOTS_INC_STOP_SIGNATURE	Indicates if the STOP_SIGNATURE section will be displayed in the DEL outbound files to LOTS.	SYS
LOTS_INC_STOP_TYPE_DESC	Include STOP-TYPE_DESC tag in XML	SYS
LOTS_LISTING_SCRIPT_NAME	Script name for LOTS XML Trip Inbound	SYS
LOTS_MINI_LODGMNT_FILE	Lodgements	SYS
LOTS_OUTBOUND_ARCH	Path for archiving outbound LOTS XML interfaces	SYS
LOTS_OUTBOUND_FAIL	Path for failing outbound LOTS XML interfaces	SYS
LOTS_OUTBOUND_PATH	Path for outbound LOTS XML interfaces	SYS
LOTS_PREVENT_MULTI_VLI_VUI	Prevent multiple VLI and VUI files being sent to LOTS (Y/N).	SYS
LOTS_SEND_PLANNED		SYS



Parameter	Description	
	Allow TRP message to be sent to LOTS when trip is still at status Planned	
LOTS_SEND_WHEN_VEHICLE_SCANNED	List of LOTS message types that will be held until a vehicle scan is received for the order.	COS
LOTS_VERSION_NUMBER	LOTS Poller Version	SYS
LOTS_XFER_EXTENSION	Sets the LOTS transfer file extension	COS
LOWERCASE_REF	Allow lowercase bill of lading	COS
MAINTAIN_SCHEDULE_DATES	Use wholesale schedule dates	COS
MANF_RECIPIENT	Indicates the recipient type of the manifest	COS
MANF_REPORT	Indicates the name of the manifest report to be automatically generated when a trip is accepted	COS
MANF_REPORT	Driver Manifest Name	COS
MANIFEST_AT_ENROUTE_ONLY	Only Send XML manifest at En-Route status	CAR
MANIFEST_ORDERS	Indicates that the cost centre allows parent and child shipments to be imported	COS
MAX_LOCATION_INACTIVE_DAYS	Maximum number of days a location can remain inactive before being set to inactive automatically.	SYS
MAX_REPORT_PARAM_VALUES	Maximum number of multiple values that can be selected for extracts	SYS
MAX_VOLUME	Maximum Volume for any FTL	SYS
MAX_WEIGHT	Maximum weight for any FTL	SYS
MCS_AWB_REQUIRED	This flag control whether the AWB (Air Way Bill) is requested during the pallet building and despatch processes in C-MCS.	SYS
MCS_DESPATCH_DISPLAY_DROP	Display the Drop Number in the Despatch Screen	SYS
MCS_DESPATCH_TO_PLAN	Enforce the despatch scanning of packages and pallets to the planned trips? (Y/N)	SYS
MCS_DISPLAY_ADDITIONAL	Display items scanned from different trips in MCS despatch? (Y/N)	SYS
MCS_DISPLAY_COMMTYPE_HAZ	This flag controls whether commodity code and hazardous information is displayed against items and pallets in C MCS pallet building.	SYS
MCS_DISPLAY_PROD_TYPE	This flag controls whether the Product Type is displayed against items and pallets in C- MCS in receipt, despatch and pallet building.	SYS
MCS_DYNAMIC_PALLET_BUILDING	This flag controls whether to allow pallet building to occur while scanning items for despatch in the items screen	SYS
MCS_EXCEPTIONS_DAMAGED	MCS exceptions at Receipt (excluding FNR and LATE) and Despatch will be marked as damaged items and be removed from onward trips (Y/N).	SYS
MCS_FAST	This parameter will control the level of validation performed during MCS scanning.	SYS
MCS_FAST_VALIDATION	Is fast validation enabled	SYS
MCS_ITEM_DISPLAY_DU	This flag controls whether the DU type is displayed instead of the item type on item lists in MCS.	SYS
MCS_LOCATION_PROMPT	Prompt for Receipt Location at Receipt	SYS
MCS_MOVE_FULL_CONSIGNMENT	Move all items for an order during MCS split scanning.	SYS
MCS_NEW_DESPATCH_MODE	This flag controls whether the new Despatch screen is run	SYS
MCS_PALLET_LABEL_FORMAT	The format of pallet label produced by the pallet building option when printing pallet labels.	SYS
MCS_PREVENT_UNPLANNED	Prevent unplanned items being scanned for pallet building, despatch and receipt although expected for the route (Y/N)?	SYS
MCS_RECEIVE_TO_PLAN	Enforce the receipt scanning of packages and pallets to the planned trips? (Y/N)	SYS



Parameter	Description	
MCS_SET_PALLET_ID	MCS set item Pallet Id	SYS
MCS_TEMPERATURE_SCAN	Prompt for Temperature Type at MCS Despatch	SYS
MCS_TENDERED_ITEMS	This flag controls whether MCS items are generated at the change to TENDERED status as well as at ACCEPTED status, or just ACCEPTED status.	SYS
MCS_UPDATE_SCAN_IMMEDIATELY	Allow items to count as despatched immediately after scanning? (Y/N)	SYS
MSC_STD_STATUS_CHANGES	Do trips go to EN-ROUTE and COMPLETED auto? Affects Despatch only. N means set to ACCEPTED if at PLANNED or TENDERED, otherwise EN-ROUTE. Any other value means set to EN-ROUTE status.	SYS
MICD_DONT_SEND_DRVR_ID	Microlise Direct Don't send driver id	CO
MICD_EE_PATH_IN_IDENT	Pattern for MICD EventExport Inbound XML	SYS
MICD_JSE_PATH_IN_IDENT	Pattern for MICD JourneySummaryExport Inbound XML	SYS
MIC_3PL_TRIP_HOURS	The number of elapsed hours that Microlise requires a trip not to exceed.	SYS
MIC_ACTUAL_DISTANCE	Will Microlise receive an actual distance from Paragon for a trip (Y/N)?	SYS
MIC_ADD_STOP_BARCODE	Include new tag STOP_BARCODE on Microlise outbound xml	SYS
MIC_ALLOW_CREATE_ORDERS	Allow orders to be created	SYS
MIC_AUTO_CONFIRM_COLLECTION_ORDERS	Create Service Types via Microlise	CO
MIC_CALC_REASON_QTY	Set the item reason quantity to the despatched quantity if a reason code is provided with a quantity of 0 instead of an accurate quantity (Y/N).	CO
MIC_COLLECTION_ORDER_TASKS	Create ad hoc orders via Microlise	CO
MIC_CONSOL_ORDERS	Consolidate the orders for the Microlise outbound XML flow, if Y then the orders will be consolidated.	CO
MIC_CONSOL_STOPS	Consolidate the stops for the Microlise outbound XML flow, if Y then the stops will be consolidated.	CO
MIC_CREATE_CD	Microlise interface to create CD reason for successful deliveries when not provided	SYS
MIC_CREATE_FAILED_ORDERS	Controls if orders be set to FAILED status on inbound Microlise flow	CO
MIC_DEBRIEF_POC	Allow the collection orders to set their POC flag when they are confirmed with actual delivered quantities and generate a ORD_COLL_XML file? (Y/N)	CO
MIC_DEFAULT_DELIVER	Should the actual times be set to the planned ones upon receipt of a STA or DEP message	CO
MIC_DEFAULT_PRODUCT_TYPE	Create Service Types via Microlise	CO
MIC_DEFINE_GROUP_NAME	Group Name For Microlise Collection Orders	CO
MIC_DEF_COST	Cost Centre default	SYS
MIC_DEF_CUST	Customer ID default for Microlise	CO
MIC_DEF_DEL_TYPE	Default Del Type for empty orders	SYS
MIC_DEF_DU_TYPE	Du Type	SYS
MIC_DEF_PRODUCT	Product Type	SYS
MIC_DELETE_REASONS	Delete Reason codes before adding new reason codes.	CO
MIC_DEL_DAY_OFFSET	Delivery Day Offset	SYS
MIC_DIRECT_DEF_COST	Cost Centre default	SYS
MIC_DIRECT_FTP_DEST_DIRECTORY	Directory for FTP of Microlise Direct Files	SYS
MIC_DIRECT_FTP_DEST_IP_ADDRESS	IP for FTP of Microlise Files	SYS
MIC_DIRECT_FTP_DEST_PASSWORD	Password for FTP of Microlise Direct Files	SYS
MIC_DIRECT_FTP_DEST_PORT	Port for FTP of Microlise Direct Files	SYS
MIC_DIRECT_FTP_DEST_PROTOCOL	Protocol for FTP of Microlise Direct Files	SYS
MIC_DIRECT_FTP_DEST_USERNAME	Username for FTP of Microlise Direct Files	SYS



Parameter	Description	
MIC_DIRECT_PATH_IN	Inbound Directory for Direct Microlise XML	SYS
MIC_DIRECT_PATH_IN_ARCH	Archive Directory for Inbound Direct Microlise XML	SYS
MIC_DIRECT_PATH_IN_FAIL	Failure Directory for Inbound Direct Microlise XML	SYS
MIC_DIRECT_PATH_IN_IDENT	Pattern for MIC Trip Inbound XML	SYS
MIC_DIRECT_PATH_IN_LIST	Filename for list of files in directory for MIC Direct XML Trip Inbound	SYS
MIC_DIRECT_PATH_IN_SCRIPT	Script name for MIC Direct XML Trip Inbound	SYS
MIC_DIRECT_PATH_OUT	Outbound Directory for Direct Microlise XML	CO
MIC_DIRECT_PATH_OUT_ARCH	Outbound Archive Directory for Direct Microlise XML	SYS
MIC_DIRECT_SEND_CUSTOMER	Microlise direct will send customer group instead of carrier	SYS
MIC_DIRECT_SEND_ROUTE_CODE	Set Microlise direct to send route code in the Journey Alias field.	SYS
MIC_DIRECT_UPDATE_PRIORITY	Flag indicating priority for del/arr updates Manual, EventExport, PodPoc updates	CO
MIC_DISABLE_EMPTY_ITEM_STOPS	Allows disabling of stops with no items on	SYS
MIC_EXCLUDE_ASSET_ID	A comma-delimited list of prefixes that determines if the new asset ID will not be stored (e.g. for loose items).	SYS
MIC_EXCLUDE_UNPACKED_LINES	Exclude any order lines that have not been packed from the Microlise files (Y/N).	CO
MIC_EXTENDED_INSTRUCTIONS	Are extended instructions sent to MICROLISE	CO
MIC_FTP_DESTINATION_DIRECTORY	Directory for FTP of Microlise Files	SYS
MIC_FTP_DESTINATION_IP_ADDRESS	IP for FTP of Microlise Files	SYS
MIC_FTP_DESTINATION_PASSWORD	Password for FTP of Microlise Files	SYS
MIC_FTP_DESTINATION_PORT	Port for FTP of Microlise Files	SYS
MIC_FTP_DESTINATION_USERNAME	Username for FTP of Microlise Files	SYS
MIC_INBOUND_ARCH	Path for Microlise XML archiving	SYS
MIC_INBOUND_CONTINUE_ON_ERROR	Continue processing MICROLISE message if invalid items exist within the file? (Y/N)	CO
MIC_INBOUND_FAIL	Path for Microlise XML failures	SYS
MIC_INBOUND_IDENTIFIER	Pattern for MIC Trip Inbound XML	SYS
MIC_INBOUND_LISTING_NAME	Filename for list of files in directory for MIC XML Trip Inbound	SYS
MIC_INBOUND_PATH	Path for yet to be processed XML files from Microlise	SYS
MIC_INC_SERVICES	List of services to be sent out to Microlise	CO
MIC_LISTING_SCRIPT_NAME	Script name for MIC XML Trip Inbound	SYS
MIC_ORDER_FULFILLMENT	Send Additional Order Fulfillment values to Microlise.	CO
MIC_OUTBOUND_ARCH	Path for archiving outbound Microlise XML interfaces	SYS
MIC_OUTBOUND_FAIL	Path for failing outbound Microlise XML interfaces	SYS
MIC_OUTBOUND_PATH	Path for outbound Microlise XML interfaces	SYS
MIC_OWNING_DEPOT	Indicates if the Microlise file is sent with Database or owning depot in the name	SYS
MIC_PACKED_DESPATCHED	Only packed/despached lines and items sent to Microlise	CO
MIC_POCPOD_NON_DEPOT	Microlise to set POC/POD for non depot orders	CO
MIC_REDUCED_EVENTS	Will Microlise receive a reduced number of defined events (Y/N)?	SYS
MIC_RESOURCE_UPDATE	Update resources on receipt of Microlise message	CO
MIC_SEND_ACCEPTED	Send Microlise Trip message when status changed to ACCEPTED	SYS
MIC_SEND_ADDR_CONTACTS	Send Contacts to Microlise (DEP/DEL/BOTH)	CO
MIC_SEND_ADD_REF	Send Address references in Microlise XML flow	CO
MIC_SEND_ALL_CONTACTS	Send All Contacts to Microlise (Y/N)	CO
MIC_SEND_CHILDREN	Are child locations sent to Microlise	CO
MIC_SEND_COST	Send Costs in Microlise XML flow	CO



Parameter	Description	
MIC_SEND_DETAIL_ID	Send DETAIL_ID in the MIC XML flow	CO3
MIC_SEND_DIRECT	Flag indicating needing to send direct message to Microlise or not	CO3
MIC_SEND_EMPTY	Are empty resources sent to Microlise	SYS
MIC_SEND_HAULIER_TYPE	Include Haulier Type in outbound microlise flow	CO3
MIC_SEND_ORD_LINE_AND_ITEM	Send both Order Lines and Items to Microlise.	CO3
MIC_SEND_ORD_REF	Send Order sub references in Microlise XML flow	CO3
MIC_SEND_SUB_TYPE	Are VAN carriers indicated	CO3
MIC_SERVICE_TASKS	Create Service Types via Microlise	CO3
MIC_SET_TO_COMP_CONF	Set trip to P-Completed, F-Confirmed, N-Neither once Microlise has finished its updates	SYS
MIC_SHIPMENT_SO_REF	Is external ref included in the Shipment detail tag?	SYS
MIC_SO_REF	So_ref sent to MICROLISE is oms_ref concatenated with external_ref	SYS
MIC_SO_REF_FORMAT	Format for the SO_REF for Microlise for non-consolidated orders: 0 = Standard (Customer Ref), 1 = Type-SO_REF-Trip-Seq-Act (eg C-12345-MAN-1234-001-L)	SYS
MIC_SO_REF_FORMAT	Format for the SO_REF for Microlise for non-consolidated orders: 0 = Standard (Customer Ref), 1 = Type-SO_REF-Trip-Seq-Act (eg C-12345-MAN-1234-001-L)	CO3
MIC_SO_REF_FORMAT	Contingency Import setting	CO3
MIC_SUPPRESS_ORDER_SEGMENT	Only show orders against the stop for the final delivery	CO3
MIC_TRUNK_CONSOL	Are trunk trips consolidated to send to Microlise	CO3
MIC_UPDATE_ACTUALS_FROM_PODPOC	Update Actuals based on POD/POC Message.	CO3
MIC_UPDATE_TO_DELIVER	Update To Deliver based on Delivered Amount	CO3
MIC_USE_ALT_STOP_ID	Prefix stop id with route code for first and last stops	CO3
MIC_USE_PALLET_ID	Use Pallet ID in Microlise	CO3
MIC_USE_STOP_ID	Determines if the stop ID or the stop sequence will be used by Microlise, if Y then the stop ID will be used.	CO3
MIC_USE_STOP_ID	Determines if the stop ID or the stop sequence will be used by Microlise, if Y then the stop ID will be used.	SYS
MILK_ROUND_ORDERS	Allow orders to be added to Milk round Routes based on delivery information	CO3
MILK_ROUND_TRIP_GENERATION	Trips Generated using milk round processing	CO3
MINIMUM_COLLECTION	Are Minimum collection charges applicable at each stop	SYS
MINS_TRUNKS_ACCEPTED	How many minutes to auto accept trunk trips?	SYS
MIN_COLLECTION_CHARGE	Minimum Collection charge per stop	SYS
MIN_CONSIGNMENT_CHARGE	Minimum charge per consignment	SYS
MIS_CHAR_SET	Character set for MIS extracts	SYS
MIS_DELETED_DAYS	The number of days after which the data on the MIS_DELETED table will be removed.	SYS
MIS_DELETE_REQUIRED	Determines whether MSI table needs to be updated	SYS
MIS_FTP_ARCH_DIR	MIS FTP archive directory	SYS
MIS_FTP_DESTINATION_DIRECTORY	MIS FTP Dir	SYS
MIS_FTP_DESTINATION_IP_ADDRESS	MIS FTP IP	SYS
MIS_FTP_DESTINATION_PASSWORD	MIS FTP Password	SYS
MIS_FTP_DESTINATION_PORT	MIS FTP Port	SYS
MIS_FTP_DESTINATION_USERNAME	MIS FTP User	SYS
MIS_FTP_PROTOCOL	MIS FTP Protocol	SYS
MIS_TAB_DELIMITER	Use a tab as a delimiter for the MIS files (Y/N)?	SYS
MIXMOVE	Is MIMOVE interface enabled?	SYS
ML_REQUIRED	Whether database is multi-lingual.	SYS
MSC_STD_STATUS_CHANGES	Do trips go to EN-ROUTE and COMPLETED auto	SYS



Parameter	Description	
MSG_CONCAT_TIME_PERIOD	Message concatenation time period (minutes)	SYS
MSG_LOC_ORD_DEL_BY_DELIVERY	Set to Y if message body for event LOC_ORD_DEL is to show delivery details	SYS
MSG_NAKS	Send an email message for NAK responses (Y/N)	SYS
MSG_NAKS_EMAIL	The email recipient for a message for NAK responses	SYS
MSG_NAKS_TYPE	A list of NAK event types to send an email message	SYS
MSG_SCHEMA_URL	XSD Schema URL Path	SYS
MSG_SCHEMA_XSD	XSD Schema XSD Name	SYS
MSG_SENDER_TRIP_ACCEPT	The sending email address for a the trip accept message.	CO
MSG_SEND_HOURS_THRESHOLD	Threshold in hours before current date when Trip messages will still be sent (using trip start date)	SYS
MSG_SUBJECT_BKNG_DTL	Message Subject for Booking Detail message	SYS
MSG_SUBJECT_BKNG_DTL_L	Message Subject for Lane Booking Detail message	SYS
MSG_SUBJECT_CTM_AUTCHASE	Message Subject for Carrier Trip Management (CTM) Auto Chase Messages	SYS
MSG_SUBJECT_CTM_MANCHASE	Message Subject for Carrier Trip Management (CTM) Manual Chase Messages	SYS
MSG_SUBJECT_LANE_ACD_DTL	Message Subject for Lane Accepted Detail message	SYS
MSG_SUBJECT_LANE_ACPTD	Message Subject for Lane Accepted message	SYS
MSG_SUBJECT_LANE_ACPTD_A	Message Subject for Lane Accepted Amended message	SYS
MSG_SUBJECT_LANE_A_DTL_A	Message Subject for Lane Accepted Amended Detail message	SYS
MSG_SUBJECT_LOC_ORD_DEL	Message Subject for Pre-warning Order delivery message	SYS
MSG_SUBJECT_MANIFEST	Message Subject for Network Rail Manifest message	CO
MSG_SUBJECT_MANIFEST	Message Subject for Manifest message	SYS
MSG_SUBJECT_MANIFEST_A	Message Subject for Manifest Amended message	SYS
MSG_SUBJECT_MANIFEST_DTL	Message Subject for Manifest Detail message	SYS
MSG_SUBJECT_MANIFEST_SUM	Message Subject for Manifest Summary message	SYS
MSG_SUBJECT_MANIFE_DTL_A	Message Subject for Manifest Detail Amended message	SYS
MSG_SUBJECT_SELF_BIL_INV	Message Subject for Self bill Credit note	SYS
MSG_SUBJECT_TENDER_INV	Message Subject for Tender Invitation message	SYS
MSG_SUBJECT_TENDER_INV_A	Message Subject for Tender Invitation Amended message	SYS
MSG_SUBJECT_TENDER_SUM	Message Subject for Tender Invitation Summary message	SYS
MSG_SUBJECT_TEND_INV_DTL	Message Subject for Tender Invitation Detail message	SYS
MSG_SUBJECT_TND_INV_DT_A	Message Subject for Tender Invitation Detail Amended message	SYS
MSG_SUBJECT_TRIP_COM_LST	Message Subject for Trip Completed List	SYS
MSG_SUB_DEPOT	Identifies the depot to replace with the current depot of the order items in the emails to invite tenders.	SYS
MSG_TRIP_CONTACT	Messaging Contact Details	CO
MTMIF_DEFAULT_CUR	Default value for DEFAULT_CUR in MTM LOCATION table.	SYS
MTMIF_DELV_SRV_CLASS_ID	Default value for DELV_SRV_CLASS_ID in MTM LOCATION table.	SYS
MTMIF_DEL_STOPTM	Default value for DEL_STOPTM in MTM LOCATION table.	SYS
MTMIF_ITEM_SOURCE	Defines what item information is uploaded to MTM into item_id column, PROD_TYPE, TEMP_COMBO or DU_TYPE	SYS
MTMIF_LOAD_CLASS_ID	Default value for LOAD_CLASS_ID in MTM	SYS



Parameter	Description	
	LOCATION table.	
MTMIF_LOAD_TYPE_SOURCE	Defines what Load information is uploaded to MTM into load_type_id column, PROD_TYPE, TEMP_COMBO or DU_TYPE	SYS
MTMIF_PICK_SRV_CLASS_ID	Default value for PICK_SRV_CLASS_ID in MTM LOCATION table.	SYS
MTMIF_PRODUCT_SOURCE	Defines what Product information is uploaded to MTM into product_id column, PROD_TYPE or NULL	SYS
MTMIF_PU_STOPTM	Default value for PU_STOPTM in MTM LOCATION table.	SYS
MTMIF_SEND_DUS	MTM Interface Send DUs - Y, N or RPE (Y sends DU Qty, RPE sends RPE Qty).	SYS
MTMIF_SEND_PIECES	MTM Interface Send Pieces - Y, N or RPE (Y sends DU Qty, RPE sends RPE Qty).	SYS
MTMIF_SEND_VOLUME	MTM Interface Send Volume - Y or N	SYS
MTMIF_SEND_WEIGHT	MTM Interface Send Weight - Y or N	SYS
MTMIF_SPLIT_CUBE	Default value for SPLIT_CUBE in MTM LOCATION table.	SYS
MTMIF_SPLIT_PALLET	Default value for SPLIT_PALLET in MTM LOCATION table.	SYS
MTMIF_SPLIT_PIECES	Default value for SPLIT_PIECES in MTM LOCATION table.	SYS
MTMIF_SPLIT_WEIGHT	Default value for SPLIT_WEIGHT in MTM LOCATION table.	SYS
MTMIF_XDOCK_HANDLING_TIME	Default value for XDOCK_HANDLING_TIME in MTM LOCATION table.	SYS
MTM_INSTALLED	MTM Installed ? - YES or NO	SYS
MTM_OPTIMISE_WAIT_TIME	Should wait time incurred at a stop be moved to end of the preceding stop if the latter is an RDC.	SYS
MTM_PATH	MTM Path	SYS
MTM_UPDATE_ORDERS	MTM Interface Update Orders - Y or N	SYS
MTM_VERSION	MTM Version	SYS
MTS_CSV_EXPORT_PATH	First path that exports looks for when writing a csv to the file system	SYS
MTS_CSV_EXPORT_PATH_ORIS	First path that exports looks for when writing a csv to the file system for ORIS	SYS
MTS_CSV_FTP_PATH	used by EXPORTS Form to set the Client Server FTP Path	SYS
MTS_CSV_IP_ADDR	CSV IP Address	SYS
MTS_CSV_LOCAL_PATH	used by EXPORTS Form in Client Server mode - sets where on users PC exports will be written to	SYS
MTS_CSV_PASSWORD	CSV Password	SYS
MTS_CSV_USER	CSV User	SYS
MTS_CSV_WEB_ADDR	CSV Web address	SYS
MTS_CSV_WEB_PATH	forms part of the URL when generating an export, different value depending on environment	SYS
MTS_CURRENT_VERSION	MTS Client Server current version	SYS
MTS_ENABLE_SECURITY	Is Security Enabled - Y or N	SYS
MTS_EXPORT_PATH	Second path that exports looks for when writing a csv to the file system	SYS
MTS_FILE_UPLOAD_URL	URL for launching the MTS File Upload	SYS
MTS_FTP_USER	Mts ftp user to be used within the stand-alone Upload/Import application.	SYS
MTS_FTP_USER_PWORD	Mts ftp user account password.	SYS
MTS_FTP_VBAPP_IMPORT_PATH	MTS Import Path for the VB ftp application	SYS
MTS_IMPORT_PATH	MTS Import Path	SYS
MTS_IMPORT_VIRTUAL_PATH	MTS Virtual Import Path	SYS



Parameter	Description	
MTS_INTERFACE	The standard file structure for interfacing	SYS
MTS_LATEST_REVISION	Latest MTS Version	SYS
MTS_LOCATION_USAGE	Controls how Locations are grouped, either via CUST_GROUP, CUSTOMER, used in Customer form to display correct tab	SYS
MTS_LOG_DIR	Path where MTS application error logs are written to	SYS
MTS_OUTBOUND_ORDER_PATH	File path for Outbound Orders .	SYS
MTS_PRODUCT_RELEASE	MTS Product RELEASE	SYS
MTS_PRODUCT_VERSION	MTS Product Version	SYS
MTS_TRACKING_SYSTEM_1	Stores the name of one of the tracking systems used in MTS	SYS
MTS_TRACKING_SYSTEM_2	Stores the name of one of the tracking systems used in MTS	SYS
MTS_TRACKING_SYSTEM_3	TomTom Tracking System	SYS
MTS_UNQ_DEPOT_DEPARTS	Do departure times need to be unique ? - Y or N	CO
MTS_WIDE_SCREEN	Should Execution screen be available in Wide Screen	SYS
NEW_ORDER_CONF	Controls if customers are emailed an order confirmation	CO
NORTHERN_MANIFEST	Depot Linked to Northern Manifests	SYS
NO_RECALC_VOL	Controls volume is calculated from the system	CO
NO_VALID_ORDS_ACPT	When Y -setting trip to Accepted will not call validate order	SYS
NULL_EXT_REF	Error if external ref is null on manual order	CO
OBS_BACKGROUND	Background Colour	SYS
OF_CURRENCY_CODE	Oracle Financial Currency Code	SYS
OF_FILE_ARCHIVE	Oracle financials archive file path.	SYS
OF_FILE_NAME_SECTION2	Stores the name of section 2 on the OF filename	SYS
OF_FILE_PATH	Oracle financials file path.	SYS
OF_FTP_DESTINATION_DIRECTORY	Oracle Financials FTP Dir	CO
OF_FTP_DESTINATION_DIRECTORY	Oracle Financials FTP Dir	SYS
OF_FTP_DESTINATION_IP_ADDRESS	Oracle Financials FTP IP	SYS
OF_FTP_DESTINATION_IP_ADDRESS	Oracle Financials FTP IP	CO
OF_FTP_DESTINATION_PASSWORD	Oracle Financials FTP Password	CO
OF_FTP_DESTINATION_PASSWORD	Oracle Financials FTP Password	SYS
OF_FTP_DESTINATION_PORT	Oracle Financials FTP Port	SYS
OF_FTP_DESTINATION_PORT	Oracle Financials FTP Port	CO
OF_FTP_DESTINATION_USERNAME	Oracle Financials FTP User	SYS
OF_FTP_DESTINATION_USERNAME	Oracle Financials FTP User	CO
OF_FTP_DEST_DTL_DIRECTORY	Cargowise Details directory	CO
OF_FTP_DEST_DTL_PASSWORD	Cargowise Details password	CO
OF_FTP_DEST_DTL_USERNAME	Cargowise Details username	CO
OF_IF_DTL	Oracle Financial IF DTL	SYS
OF_IF_FTR	Oracle Financial IF FTR	SYS
OF_IF_HDR	Oracle Financial IF HDR	SYS
OF_JRNL_ENTRY_SOURCE_NAME	Oracle Financial Journal Entry Source Name	SYS
OF_ORIGID	Stores the name of ORIGID	SYS
OF_SECTION2	Stores the name of section 2 on the OF filename	SYS
OF_SETTINGS	Controls if Oracle Financial settings are required for 11i and R12	SYS
OF_SOURCE_SYSTEM_CODE	Oracle Financial System Code	SYS
OMS_ACTUALS_MANDATORY	Governs which ACTUAL_QUANTITY fields require mandatory population in Debrief forms.	SYS
OMS_ADD_ORDER_TO_LOCS	Should orders added to a Trip be added to existing stops based on Location Id - YES or NO	SYS
OMS_ADD_ORDER_TO_MILK	Allow orders to be added to Milk round Routes	CO



Parameter	Description	
OMS_ADD_PACKED_LINE	Allow an order to be valid when it contains an order line with a planned qty of zero? (Y/N)	COS
OMS_ALLOW_DUPL_CUST_REF	This parameter when set will allow the duplicate customer references	SYS
OMS_ALLOW_MANUAL_SCHEDULE	Display Manual Schedule Flag in orders screen	COS
OMS_ALTERNATE_REBOOK	Alternative Rebook Functionality	COS
OMS_AMEND_SVC_FLAGS	OMS_AMEND_SVC_FLAGS	SYS
OMS_AVG_WEIGHT	Uses average weight to calculate the weight against an order	COS
OMS_CHANGE_DEL_TYPE	List of Delivery types allowing change	SYS
OMS_CHECK_CUTOFF	Controls if cut of times for product and du are considered when creating orders	SYS
OMS_CONSOLIDATE_DUPLICATE_LINES	Enables the consolidation of duplicate order lines during order entry (Y/N).	COS
OMS_CONSOL_ITEMS	Controls if items are consolidated in order xml	COS
OMS_CONTACT_TRACKING	To control the use of the order and location contacts for the contacts when they are sent to EPOD and Portal TTM.	SYS
OMS_CREATE_DUMMY_SOL	Create dummy SOL records for Dunelm	SYS
OMS_CREATE_POD	Create CSV POD files for the customer? (Y/N)	CUS
OMS_CUTOFF_TIME_DEFAULT	Sets the default cut-off time in format HH24:MI for the order time window calculation should a schedule rule not exist for the locations.	SYS
OMS_DEFAULT_ORDER_CREATION	Controls dates needed when creating Orders in Orders form. ALL, COLLECTION, DELIVERY or STANDARD	SYS
OMS_DEFAULT_SERVICE_LEVEL	Default service level for the derivation of the time windows for parcel orders.	COS
OMS_DEFAULT_TEMPLATE_METHOD	Default method for generating orders from order template screen (M for Multiple, S for Single)	SYS
OMS_DEF_PROD_TYPE	Default Prod Type for Dunelm	SYS
OMS_EXCLUDE_AUDIT	Exclude changes to field from audit	SYS
OMS_FOOTPRINT_FOR_VOLUME	Will the footprint of the order line be include in the VOLUME item for the outbound XML file for the despatch units instead of the cubic volume (Y/N)?	COS
OMS_INCLUDE_X_ITEM_PREFIX	Allow items with a prefix of X to be included in the Load Management screen and Microlise files (Y/N)?	COS
OMS_INVALID_SAME_LOCS	Set the order status to INVALID when the from and to locations are the same (Y/N)	SYS
OMS_ITEMS	Generate Item Identifier using OMS reference and count of items	COS
OMS_ITEM_AKA_DISPLAY	Controls the label on the AKA Code field	COS
OMS_LEAVE_AS_NEW	To indicate if orders currently at status NEW are to be left at that status after validation other than the paragon interface? (Y/N)	SYS
OMS_MIC_DEL_DATE	Are MIC files generated when delivery windows are updated	SYS
OMS_NO_LIFTS	Controls if lifts are included in order xml	COS
OMS_NO_TRIP_REF_TRG	Do not obtain trip information in order triggers	SYS
OMS_OFFERED_EARLY_OFFSET	The number of hours (minus) to offset the early collection or delivery time for the order when its booking status is OFFERED.	COS
OMS_OFFERED_LATE_OFFSET	The number of hours (plus) to offset the late collection or delivery time for the order when its booking status is OFFERED.	COS
OMS_ORDER_ARCH_DEL_DAYS	Number of days that archived Order Audit messages will be retained for.	SYS
OMS_ORDER_AUDIT_ARCH_DAYS		SYS



Parameter	Description	
	Number of days that Order Audit message should be retained in the main table before being archived.	
OMS_ORDER_ID	Use the OMS Ref for the Order ID	CO3
OMS_RECALC_OH_RPE	Recalculate the planned and packed RPE when an order is validated (Y/N).	CO3
OMS_RESET_AUTO_PROC	Will the auto-processed flags of the order for the scheduling engine be reset when the early delivery date and time is changed? (Y/N)	CO3
OMS_RE_BOOK_STATUS	Controls the status of re-book orders to DEL_FUTILE	SYS
OMS_SEQ_CTL_ITEM_FORMAT	Add a prefix for the OMS reference for the order items as well as a sequential number (Y/N)	SYS
OMS_SESSION_EARLY	Earliest arrival offset before the end of the handling time	SYS
OMS_SESSION_HANDLING	Handling time associated with session collections	SYS
OMS_SESSION_LATE	Latest arrival offset after the end of the handling time	SYS
OMS_SESSION_WINDOW	Percentage value used to calculate the collection date and time window for transport orders generated from sessions	SYS
OMS_SET_DATES	Change Delivery dates on Invalid Back orders	CO3
OMS_SET_DELIVERY_TYPE	Order on/off/not in Schedule	CO3
OMS_STD_ITEMS	Controls if Standard items are auto generated	CO3
OMS_STD_RULE	Schedule rules applied excluding transport mode and delivery types	SYS
OMS_TAG_TO_ASSET_TYPE	Order types to be validated in TAG to Asset Scanning	SYS
OMS_TRACK_ITEMS	Indicates if the tracking references will be stored as order items. (Y/N)	CUS
OMS_TRACK_ITEMS	Indicates if the tracking references will be stored as order items. (Y/N)	CO3
OMS_UNIQUE_EXT_REF	Controls if imports can load multiple order lines	CUS
OMS_UPDATE_SCHEDULE_TO_TRIP	Update the time windows for the orders that exist on a trip when the schedule of the trip is changed in the Planning screen.	SYS
OMS_VALIDATE_INACTIVE_CODES	To validate orders with error condition for an invalid code for delivery type and service level	SYS
OMS_VALIDATE_TEMPLATE	Controls whether the Template Id is populated with the associated Lane Id - LANE or NULL	SYS
OPEN_FTP_DESTINATION_DIRECTORY	OPEN FTP destination Directory	SYS
OPEN_FTP_DESTINATION_IP_ADDRESS	OPEN FTP destination IP Address	SYS
OPEN_FTP_DESTINATION_IP_ADDRESS_COPY	OPEN FTP destination IP Address	SYS
OPEN_FTP_DESTINATION_PASSWORD	OPEN FTP Password	SYS
OPEN_FTP_DESTINATION_PORT	OPEN FTP destination Port	SYS
OPEN_FTP_DESTINATION_USERNAME	OPEN FTP Username	SYS
OP_SYS	Operating system	SYS
OP_SYS_VER	Operating system version	SYS
OR3_INTERFACE	Is the PR3 interface active	SYS
ORDER_SEARCH_CONSOL	Include orders that have passed through a user's SCHED GROUP	SYS
ORDER_WELL_HIGHLIGHT	Highlight Orders where matching trip found	CO3
ORD_ALLOW_SHIPMENTS	Consolidate Orders on Shipments	CO3
ORD_BOOKING_METHOD	CSV Import - Booking Method -HOME for home delivery, any other value for standard	CO3
ORD_BOOKING_STATUS	Controls if Booking status is displayed	CO3
ORD_CHANGE_BOOKING	Controls if a change to the booking ref is reflected on the payment	CO3
ORD_CHECK_DUPLICATE_ORDERS	For orders where source system is IMPORTS check to see if order is a duplicate - Y or N	SYS



Parameter	Description	
ORD_CLEAR_DATES	Are dates cleared in the interface	SYS
ORD_CONF_REPORT	Ord Conf report	COS
ORD_COPY_ALL_REFS	Are all references copied when items are split?	SYS
ORD_CREATE_MANIFEST	Controls if a portal manifest record is created for Manual Orders	COS
ORD_CREATE_PORTAL_ITEM_IDS	Does C-TMS generate the item identifiers for Portal orders	SYS
ORD_CREATTE_PORTAL_ITEM_IDS	Does C-TMS generate the item identifiers for Portal orders	SYS
ORD_DEBRIEF_DAYS	Default number of days used to restrict Orders displayed by Order Debrief form.	SYS
ORD_DEFAULT_AIR	Default Dimensional Weight Factor for Air Transport	SYS
ORD_DEFAULT_CC	Order Default Cost Centre	SYS
ORD_DEFAULT_CUST	Order Default Customer	SYS
ORD_DEFAULT_DEL_TYPE	Order Default Delivery Type	SYS
ORD_DEFAULT_ROAD	Default Dimensional Weight Factor for Road Transport	SYS
ORD_DEFAULT_SEND_TO_MTM	Order Default Send to MTM Flag	SYS
ORD_DEFAULT_SESSION_DU_TYPE	Standard delivery unit used to transport unprocessed blood from sessions	SYS
ORD_DEFAULT_SESSION_PROD_TYPE	Standard product type used to transport unprocessed blood from sessions	SYS
ORD_DEFAULT_TRANSCODE	Order Default Trans. Code	SYS
ORD_DESP2_RESEND	Allow Desp2 message to be resent from orders screen	COS
ORD_DISPLAY_LIFTS	Display Lifts in preference to quantity	SYS
ORD_EARLY_COLLECT_THRESHOLD	Number of Hours Early Collection Time can be before the Current Date/Time when creating an Order	SYS
ORD_EDIT_RPE	Enable the RPE of an order line to be edited? (Y/N)	COS
ORD_EFFECTIVE_FUEL	Indicates if Fuel charges are fixed or based on effective dates	COS
ORD_END_TIME	The default late delivery time when a route is not provided for an API order (HH:MM)	SYS
ORD_ENHANCED_REBOOK	Controls which rebook screen is displayed in the orders form	COS
ORD_EQUIPMENT_LOAD	Controls if equipment & equipment times are validated	SYS
ORD_FIXED_SCHEDULE_CHECK	Check for existing fixed schedule generated orders	CUS
ORD_FUTURE_LIMIT_DAYS	Maximum Number of days in the future that an order can be created	SYS
ORD_FUTURE_OFFSET	How far in the future can order offset be set	COS
ORD_IGNORE_LINE	Are some order lines ignored in the interface	SYS
ORD_JUST_IN_TIME	Is the collection window set just in time	CUS
ORD_LATE_TIME	Late time windows for generated stack orders	SYS
ORD_LINE_LENGTH	Store LENGTH i/o FOOTPRINT	COS
ORD_LINE_METHOD	Line Qty Calc Method	COS
ORD_LINK_CONTENTS	Link Items and contents in the interface	SYS
ORD_NO_DEL_FOR_FAILS	Controls if DEL messages are generated for FAILED orders - Y to prevent, C to send as CAN	COS
ORD_OMIT_PACK_SCHEDULING	Omit the scheduling of the order and only print the label when pack confirming.	COS
ORD_ON_SCHED_DEL_LOC	Du category to be assessed for exclusion from parcel scheduling	CUS
ORD_POSTCODE_SEARCH	Determines whether the user can search for order addresses via a postcode (Y/N).	SYS
ORD_PROCESSED_MSG	Ord Conf Processed Email Msg	COS
ORD_PROCESSED_SUBJECT	Ord Conf Processed Subject	COS



Parameter	Description	
ORD_QUANTITY_DU_FIELDS_FORMAT_MASK	Default quantity and pallet fields format mask	SYS
ORD_QUANTITY_PALLET_FIELDS_FORMAT_MASK	Default quantity and pallet fields format mask	SYS
ORD_RBO_PREFIX	Is the rebook prefix stripped for LOTS?	SYS
ORD_REASON_CODE_FILTER	Order Reason Code Filter	SYS
ORD_REASON_SUP	Reason codes to be suppressed in the web service	CO
ORD_RECEIVED_MSG	Ord Conf Received Email Msg	CO
ORD_RECEIVED_SUBJECT	Ord Conf Received Subject	CO
ORD_REMOVE_CANC	Controls if Orders Cancelled in C-TMS generate REM message to LOTS	CO
ORD_REPRINT_PACK_VISIBLE	Determines whether the Reprint Labels and Pack Confirm buttons are visible. (Y/N).	SYS
ORD_RETAIN_PLANNED	Planned weight is retained on lines	CO
ORD_RPE_LM_FACTOR	The factor for loading meters to calculate the RPE of the orders.	CO
ORD_SET_BUSINESS_TYPE	Set Business Type on Orders	CO
ORD_SET_SERVICE	Controls if the service level is set to match the delivery type	SYS
ORD_SPLIT_ALL_REFS	Are all references copied when items are split?	SYS
ORD_SPLIT_REBOOK_ITEMS	Controls if items on the original order suffixed with X when the order is re-booked	CO
ORD_SPLI_ALL_REFS	Are all references copied when items are split?	SYS
ORD_STACK_DEBRIEF	Order Stack Debrief	CO
ORD_START_TIME	The default early delivery time when a route is not provided for an API order (HH:MM)	SYS
ORD_TARGET_SEND_TO_MTM	Order Target Send to MTM - Y or N	SYS
ORD_TEMPERATURE_COMBO	Use Temperature Combo to determine if the customer reference should be highlighted.	CO
ORD_TEMPLATE_EDIT_UPDATE	Controls whether the user can edit the order template data during generation (Y/N).	SYS
ORD_UNCHEDULE_FAILS	Controls if Orders Cancelled in EPOD generate a CANC message to LOTS	CO
ORD_UNSCHD_COMP	Controls if Orders with 0 qty delivered be unscheduled from COMPLETED trips?	CO
ORD_UPDATE_LATE_COLL_DATE_TO_DEL	Controls if the Late Collection Date/Time is updated at Save to Match the Late Delivery Date/Time.	SYS
ORD_VALIDATE_GROUP_NAME	Validate Group Name during order entry	CO
ORD_WRITE_NOTES	Write Order Notes.	SYS
ORD_XDOCK_LOTS_DEL_MSG	Lots DEL msg is only sent on last trip for xdock orders (Y/N)	SYS
ORS_DELIMITER	Oracle reporting suite data field delimiter	SYS
ORS_SUMMARY	Allow the summarisation OF ORS reports	SYS
ORS_TYPE_DEF_GROUP_BY	List of the ORS types to default group by fields	SYS
ORS_TYPE_EXC_GROUP	Exclude ORS types from grouping fields	SYS
OST_DEBRIEF_WARNING_DAYS	Number of days prior to current date for which orders not debriefed will included in warning message in Order Tracking form.	SYS
OUTBOUND_3	File path for Outbound Trips.	SYS
P2	users	SYS
PALLET_BASED_RATING	Rate based on chargeable/non chargeable pallets	CU
PARAGON_IMPORT_LAYOUT	Paragon Import Layout	CO
PARAGON_INSTALLED	Paragon Installed ? - YES or NO. Only one of MTM_INSTALLED or PARAGON_INSTALLED should be set to YES.	SYS
PARAGON_INSTALLED	Paragon Installed ? - YES or NO. Only one of MTM_INSTALLED or PARAGON_INSTALLED should be set to YES.	CO



Parameter	Description	
PARAGON_RUNNING	Paragon Import is currently running (to stop outbound XML jobs)	SYS
PARAGON_SCHED_DAYS	Determines how many days back paragon should extract records	CO3
PAR_ALLOW_IMPORT_UNDO	Used to indicate if the UNDO button is allowed to be pressed on the Paragon Trip Import? (Y/N)	CO3
PAR_API	Create Control records for Paragon API	SYS
PAR_AUDIT	Include auditing of the import process in the STP version of the Paragon API (Y/N)	SYS
PAR_AUTO_RESET_NEW	Auto reset orders at status New after paragon run	CO3
PAR_CHECKSUM_OFF	To indicate if the checksum validation code is required for paragon imports? (Y/N)	SYS
PAR_DISPLAY_IMPORT_DETAILS	Used to indicate whether the additional message containing the imported details is displayed or not on the Paragon Trip Import? (Y/N)	CO3
PAR_DUN_COL_END_OFFSET	Offset for Dunelm collection end time	SYS
PAR_DUN_COL_START_OFFSET	Offset for Dunelm collection start time	SYS
PAR_DUN_TRUNK_CUTOFF_TIME	Set a cut-off time in format HH24:MI to apply to trunk trips to use the current schedule for the day.	SYS
PAR_DUN_TRUNK_OFFSET_DAYS	Set a number of days to assess the trunk trips for the DUN radial trips.	SYS
PAR_ENDPOINT_URL	URL for paragon API	SYS
PAR_EXPORT_FORECAST	Send forecast values to Paragon	CO3
PAR_FREQUENCY	Frequency for PAR Master keys	SYS
PAR_FTP_DESTINATION_DIRECTORY	Directory for FTP of Paragon Files	SYS
PAR_FTP_DESTINATION_IP_ADDRESS	IP for FTP of Paragon Files	SYS
PAR_FTP_DESTINATION_IP_ADDRESS_OLD	IP for FTP of Paragon Files	SYS
PAR_FTP_DESTINATION_PASSWORD	Password for FTP of Paragon Files	SYS
PAR_FTP_DESTINATION_PORT	Port for FTP of Paragon Files	SYS
PAR_FTP_DESTINATION_USERNAME	Username for FTP of Paragon Files	SYS
PAR_GROUP_STAGING	Paragon Group Staging Level	SYS
PAR_INBOUND_ARCH	Path for Paragon XML archiving	SYS
PAR_INBOUND_FAIL	Path for Paragon XML failures	SYS
PAR_INBOUND_IDENTIFIER	Pattern for Paragon Trip Inbound XML	SYS
PAR_INBOUND_LISTING_NAME	Filename for list of files in directory for Paragon XML trip Inbound	SYS
PAR_INBOUND_PATH	Path for yet to be processed XML files from Paragon	SYS
PAR_INT_SCREEN_CLASSIC_LAYOUT	Removes/Renames fields in PAR_INT to traditional C-TMS system setup rather than those changed for industrial	SYS
PAR_KEY_FORMAT	PAR Master key format WKXX, DDMM, DAYX	SYS
PAR_KEY_PROJECT	PAR Project name	SYS
PAR_LISTING_SCRIPT_NAME	Script name for Paragon XML Trip Inbound	SYS
PAR_OUTBOUND_ARCH	Path for archiving outbound Paragon XML interfaces	SYS
PAR_OUTBOUND_FAIL	Path for failing outbound Paragon XML interfaces	SYS
PAR_OUTBOUND_PATH	Path for outbound Paragon XML interfaces	SYS
PAR_PLAN_DIRECT	Controls if Paragon will plan direct collections (Not to owning depot)	CO3
PAR_PROXY	Paragon Proxy Server	SYS
PAR_RUN_NUMBER	Is Paragon Planning based on Run Numbers?	SYS
PAR_SEND_ALL_LOCATIONS	Are locations sent out via API	SYS
PAR_SET_ALL_FROM_NEW	Should all orders and trips set as NEW be updated after Paragon Run	SYS
PAR_SHUNT_TRUNK	Check if the shunt and trunk routing has been completed prior to exporting to Paragon (Y/N).	SYS
PAR_SLOT_CUTOFF_TIME		SYS



Parameter	Description	
	Number of minutes before slot window start that it closes to new orders	
PAR_START_DATE	Start Date for Master Keys	SYS
PAR_TENNANT	Tenant for paragon API	SYS
PAR_TENNANT_KEY1	Tenant KEY 1 for paragon API	SYS
PAR_TENNANT_KEY2	Tenant KEY 2 for paragon API	SYS
PAR_TRIP_STATUS	Controls the status of any Trips that are created via the Paragon Interface.	SYS
PAR_TRUNK_THRESHOLD_UOM	Controls the order qty measure used as a threshold when assigning orders to Trunk trips in the Paragon Import. Values are WEIGHT, RPE or VOLUME.	COS
PAR_TRUNK_TRIP	Are trunk trips generated from Paragon Plan	SYS
PAR_USE_LOC	Paragon Use From location of order s depot	SYS
PAR_USE_RPOXY	Paragon Use Proxy	SYS
PAR_USE_SLOTS	Use slots when exporting to Paragon (DUN format)	SYS
PAR_VIRTUAL_OUT_ARCH	Path for webshow of archiving outbound Paragon XML interfaces	SYS
PAR_VIRTUAL_OUT_FAIL	Path for webshow of failing outbound Paragon XML interfaces	SYS
PAR_XML_OLD_ORDERS	Number of days in the past to still be included for sending orders to paragon	SYS
PERCENTAGE_MARGIN	Percentage Margin Value	SYS
PETAL_STARTS_AT_ANY_DEPOT	Does a Petal start at a Depot ?	SYS
PLANNING_AUTO_SCHED_INACTIVE_DEPOTS	List the inactive depots by commas and in single quotes to exclude their orders in the Planning screen.	SYS
PLAN_REG_COUNTRY	Planning Region Country suffix	COS
POLAR_CUST_REF	Controls the source of cust ref in Polar Speed labels	CUS
POM_DATE_END	Number of days after Purchase Order dates	SYS
POM_DATE_START	Number of days before Purchase Order dates	SYS
POM_DEF_COST	Default Cost Centre for PO	SYS
POM_DEF_CUST	Default Customer for PO	SYS
POM_DEF_PROD_TYPE	Default Product Type for PO	SYS
POM_INBOUND_ARCH	Path for processed XML files that have successfully completed processing, see: int_po_inbound_header	SYS
POM_INBOUND_FAIL	Path for processed XML files that have failed processing for reasons described against int_po_inbound_header	SYS
POM_INBOUND_PATH	Path for yet to be processed XML files	SYS
POM_OUTBOUND_ARCH	Path for processed POM outbound XML files that have successfully completed processing	SYS
POM_OUTBOUND_PATH	Path for PO outbound files	SYS
PORSCHE_DOT_CODE	Tyre Age for PORSCHE	SYS
PORTAL_AUTO_SCHED_RET_DAYS	Day range for auto allocation of return orders	SYS
PORTAL_DEF_DEL_TYPE	Delivery Type for Return orders	SYS
PORTAL_ORDERS	Portal Imports available	SYS
POSTAL_STRINGS_TOWN	Is town compared in postal string zones	SYS
POSTCODE_SHIPMENTS	Indicates if shipments are postcode based	COS
PO_OVERRIDE_DU_WITH_SUB	A comma-separated list of transit DU types for which the sub-transit DU type will be used instead to generate order lines for the PO	SYS
PRD_ITEM_IMPORT_FILE	Name of Product Item Import file	SYS
PRD_ITEM_IMPORT_PATH	Product Item Import path	SYS
PREVENT_ORD_COL_AFTER_DEL	Stop any ORD or COL messages after a DEL message	COS
PRINT_ACCEPTED_LABEL	Controls if customer labels are printed when trip is Accepted	COS



Parameter	Description	
PRINT_INBOUND_LABELS	Controls if labels are generated for inbound xml orders	SYS
PRINT_LABEL	Controls if customer labels may be reprinted from Order screen	CO
PRINT_LABEL_PATH	File path for Parcel Carrier Labels to be printed	SYS
PROJECT_LOCATIONS	Indicates which prefixes are used for project location ids	CO
PTV_RO_ARCH_DIR	Folder for archive of PTV RO files	SYS
PTV_RO_AUTO	PTV Automatic Response from Import	SYS
PTV_RO_DEL_PRIORITY_DAYS	Number of days before late delivery when prioritized in Route Optimiser	SYS
PTV_RO_DIR	Folder for PTV RO files	SYS
PTV_RO_EXTEND	PTV plan covers more than 1 week	SYS
PTV_RO_FILE_API	Create File or send data via API	SYS
PTV_RO_FIX_MINUS1	Reduce fix time by 1 when sending to PTV RO	SYS
PTV_RO_GROUP_NAME	Select PTV unscheduled orders by group name rather than depot	SYS
PTV_RO_MASTER_PROFILE	Profile for PTV RO webservice	SYS
PTV_RO_MASTER_PROFILE_DEPOT	Profile for PTV RO webservice	SYS
PTV_RO_ORDER_PAIRS	PTV Send load and unload tasks combined	SYS
PTV_RO_ORD_FUTURE_DAYS	PTV Orders Future Days	SYS
PTV_RO_ORD_HISTORIC_DAYS	PTV Orders Historic Days	SYS
PTV_RO_PASSWORD	Password for PTV RO webservice	SYS
PTV_RO_PASSWORD_BETA	Password for PTV RO webservice	SYS
PTV_RO_PROFILE	Profile for PTV RO webservice	SYS
PTV_RO_PROFILE_DEPOT_SCHED	Profile for PTV RO webservice	SYS
PTV_RO_PROJECT	Project for PTV RO webservice	SYS
PTV_RO_PROXY	Proxy server name for PTV RO webservice	SYS
PTV_RO_SEND_RETRO	Send retro orders	SYS
PTV_RO_SET_ROUTE	Set route code on trips from PTV RO	SYS
PTV_RO_SPLIT	PTV imported route returns to Start Depot	SYS
PTV_RO_TIMEOUT	Timeout for PTV RO webservice	SYS
PTV_RO_TRIPS_HISTORIC_DAYS	PTV Trips Historic Days	SYS
PTV_RO_TRIP_FUTURE_DAYS	PTV Trips Future Days	SYS
PTV_RO_URL	URL for PTV RO webservice	SYS
PTV_RO_URL_BETA	URL for PTV RO webservice	SYS
PTV_RO_URL_NHS	URL for PTV RO webservice	SYS
PTV_RO_USERNAME	Username for PTV RO webservice	SYS
PTV_RO_USERNAME_BETA	Username for PTV RO webservice	SYS
PTV_RO_USERNAME_NHS	Username for PTV RO webservice	SYS
PTV_RO_WAIT_TIMEOUT	Timeout for PTV RO webservice Response	SYS
RADIO_DU	Radio active	CO
RDT_441_CHECK_DAYS	Set a number of days in which to assess the prior loading messages for WCS.	SYS
REBOOK_ALT_STATUS	If set to Y when an order is rebooked the original orders status will not be changed	SYS
REBOOK_COPY_SUB_REF_CONTACTS	Set as Y or N to copy Sub References on Rebook, contact details only i.e. SMS and Email details	CO
RECORD_LIMIT	Limitation of records to display on Customer Service Screen	SYS
REFRESH_WHEN_CLOSE_ORDER_DETAILS	Refresh the order summary screen when you close the order details page in the Orders form	SYS
REPORT_CONNECT_STRING	Report auto production - connect string (user/pass@database).	SYS
REPORT_DIRECTORY	Report auto production - place report in directory.	SYS



Parameter	Description	
REPORT_FLOC	Report auto production - name of FLOC directory for reports.	SYS
REPORT_IP_ADDRESS	Report auto production - IP address server.	SYS
REPORT_PORT	Report auto production - Port	SYS
REPORT_SERVER	Report auto production - name of report server.	SYS
REP_DELIVERY_DOCS	Name of the Delivery report printed from trip tree	COS
REP_JAVA_PDF	Java Report Controller Script	SYS
REP_JAVA_PDF_DIR	Java Report Folder	SYS
REP_JAVA_PDF_SHOW	Java Report Webshow Folder	SYS
REP_LOADING	Name of the loading report printed from trip tree	COS
REP_ORARRP_DEST_FILEPATH	Reports Destination Filepath	SYS
REP_ORD_EXTRACT_DAYS	Number of days that the order extract can be run for	SYS
REP_PDF_DEST_FILEPATH	Reports PDF File Path	SYS
REP_PDF_FILE_LOC	Reports PDF file location	SYS
REP_PDF_WEB_DEST_NAME	Reports PDF destination	SYS
REP_PDF_WEB_SERVER_NAME	Reports PDF Web Server Name	SYS
REP_PDF_WEB_SERVER_URL	Reports PDF Web Server URL	SYS
REP_SERVER_WEB	Reports Server	SYS
REP_SHOW_CARRIER	Controls if Carrier id is included in the Unshed Orders report	SYS
REP_SO_REF_FORMAT	Set as 1 or 0 to reformat Order Reference, extract all characters up to the first '-' or '_'	COS
REP_WEB_SERVER_NAME	Reports Web Server name	SYS
REP_WEB_SERVER_URL	Reports Server URL	SYS
RESEND_EFX_STATUS	Can users resend EFX at status Accepted and En-route	COS
RESOURCE_DIARY	Resource Diary for display of trip allocation	SYS
RES_ALTERNATIVE_CARRIER	During MTM sync, if Carrier does not exist should MTS check for alternative carrier ? - Y or N	SYS
RES_ALT_CARRIER	Controls access to Alternate carriers button on Resource form, these are used in TRIPSUM_JRL. - Y or N	SYS
RES_AVAILABILITY_ALLOC	Determines how resources are allocated to a trip	COS
RES_CONTROL_ALLOC_RESOURCE	Controls whether a resource can be assigned to more than one Carrier / Carrier Group	SYS
RES_DT_FUEL_UNITS	Current fuel unit - Litres or Gallons	SYS
RES_EXTERNAL_DRIVER	Use External Drivers	SYS
RES_TRACKING_SYSTEM_DISPLAYED	Null, Tractor, Trailer or Both to indicate if Tracking systems are enabled.	SYS
RETAIN_INTERFACE_ERRORS	Number of days Interface Errors are retained	COS
RE_PLAN_ORDERS	Controls if the Planner splits order for planning	SYS
RE_SEQUENCE_STOPS	Are trip stops validate	COS
RHA_INDEXES	Use RHA indexes	SYS
RICO_ACCOUNT	Rico Account login to Star-Gate	SYS
RICO_OUT_ARCH	Outbound archive folder for Rico XML files	SYS
RICO_OUT_DIR	Outbound folder for Rico XML files	SYS
RTE_CHECK_MISSING_STOPS	Determines which stops must be present on a Trip, either HIGHEST_OPTIONAL or ALL.	SYS
RTE_DEF_CAPACITY_MEASURE	Fixed Routes, default capacity measure (RPE, WEIGHT or VOLUME)	SYS
RTE_DISBAND_SEMI_HOURS	Sets the number of hours prior to departure when a SEMI_FIXED Trip should be disbanded	SYS
RTE_LOG_DEL_DAYS	Number of days that Fixed Routes log messages should be kept for	SYS
RTE_MAINT_RDC_ALL_USAGE	Allow the values for the fixed route locations to include an RDC location when the depot has not been	SYS



Parameter	Description	
	assigned to a customer or a customer group (Y/N)	
RTE_ORDERS_ASC_OR_DESC	Should orders be orders in Ascending or Descending order (ASC or DESC)	SYS
RTE_PLAN_BY_REGION	Allow Fixed Routes to plan by Postal Region or Planning Region, values are PL and PO.	SYS
RTE_PRIORITISE_URG_LATE_ORDS	Controls whether urgent and late orders are to prioritised in the Fixed Route process.	SYS
RTE_REGION_AND_ZONE	Will fixed routes crossdock by planning region and location zone? (Y/N)	SYS
RTE_SCHED_OFFSET_HRS	Fixed Routes Schedule Offset in hours	SYS
RTE_SEMI_FIXED_CAPACITY	Determines whether capacity is checked by FILL or TRAILER capacity.	SYS
RTE_SEMI_FIXED_FUNCTION	Should trips go to SEMI_FIXED if they are not optimum, Y or N.	SYS
RTE_STOPOVER_MINS	Default number of minutes for a stopover for the network route.	COS
RTE_TRIPS_DEL_DAYS	Fixed Route RTE Trips in status DELETED on schedules older than this value will be deleted	SYS
RTE_TRIPS_FIN_STATUS	Fixed Routes final status	SYS
RTE_TRIPS_TO_ACCEPTED	Defines if ACCEPTED or PLANNED Trips are deleted in Rev TI, if yes then ACCEPTED, otherwise PLANNED - Y or N	SYS
RTE_USE_CROSSDOCK	Should Fixed Routes allow crossdocks to be used.	SYS
SALES_EXPORT	Payments are to be exported	SYS
SAP_DEFAULT_DU_QTY	Default DU Quantity for bookings received via the SAP Interface.	SYS
SAP_DEFAULT_DU_TYPE	Default DU Type for bookings received via the SAP Interface.	SYS
SAP_DEFAULT_PROD_TYPE	Default Product Type for bookings received via the SAP Interface.	SYS
SAP_POD_MSG_RQD	Is SAP (POD) Messages Required to be Extracted out of MTS - Y or N.	SYS
SCHEDULE_RULES_SERVICE	Is service level displayed in schedule rules	COS
SCHED_ENG_DEL_OFFSET	The number of days that the order will remain in the delivery depot before it can be assigned to its delivery trip	COS
SCHED_ENG_DEL_OFFSET_CUTOFF	The cut off time at the delivery depot before an order can be assigned to its delivery trip	COS
SCHED_ENG_EXC_DU_CATEGORY	Du category to be EXCLUDED from parcel scheduling	CUS
SCHED_ENG_PART_PLAN	Will the network scheduling engine allow orders to be partially planned?(Y/N)	COS
SCHED_EXC_SI	Exclude order with special instructions from engine	COS
SCHED_RULE_SHOW_ZONE	Display zones instead of master location on delivery schedules in Sched Rules form	SYS
SCH_CSCS_EST_IMPORT_FILE	Name of CSCS Estimate Import file	SYS
SCH_CSCS_FC_IMPORT_FILE	Name of CSCS Forecast Import file	SYS
SCH_CSCS_IMPORT_PATH	CSCS Import path	SYS
SCH_DEFAULT_FIXED_TEMPLATE	Default Fixed Template Name for Auto Generation	SYS
SCH_DELETE_PROD_QUANT_DURATION	Number of days worth of Product Quantity data that gets deleted.	SYS
SCH_MANUAL_CREATE_SCHED	Ability to manually create schedules - Y or N	SYS
SCH_NAME_FORMAT	Schedule Name Format	SYS
SCH_RECORD_ITEM_DU_USE	Determine whether to update avg used flag and DU data on product quantity. This might be switched off to improve performance - Y or N	SYS
SCH_SCHEDULE_ADV_DAYS	Determines how many days in advance to generate fixed routes Schedule	SYS



Parameter	Description	
SCH_SCHED_DATE_RANGE	Range in days for displaying schedules	SYS
SCH_SCHED_DURATION	Schedule Duration (Days)	SYS
SCH_SCHED_ORD_DERIVE	Controls the Order Schedule Date. Acceptable values ECDT, LCDT, EDDT, LDDT.	SYS
SCH_SCHED_ORD_IMP_IGGESUND_SCHED_DATE_OVERRIDE	When Importing IGGESUND data, can the sched_date be over-written by the SCH_SCHED_ORD_DERIVE rule?	SYS
SCH_SCHED_ORD_IMP_TI_ORDER_SCHED_DATE_OVERRIDE	When Importing TI_ORDER data, can the sched_date be over-written by the SCH_SCHED_ORD_DERIVE rule?	SYS
SCH_SCHED_START	Schedule Start time	SYS
SCH_TRIP_ID_DEPOT	Controls if Trip ID is derived from Owing Depot	SYS
SCH_TRIP_ID_FMT	SCH Trip Id FMT	SYS
SCH_TRIP_ID_PREFIX	Prefix for Depot based Trip ID	SYS
SCH_VLS_IMPORT_FILE	Name of VLS Import File	SYS
SCH_VLS_IMPORT_PATH	VLS Import Path	SYS
SCR_CURRENT_HIGHLIGHT_COLOUR	Controls colour of highlighted rows in tables	SYS
SCR_HEADER_BKG_COLOUR	Colour for header toolbars on forms	SYS
SCR_HEADER_BMP_PATH	Location of BMP to control the colour of the toolbar/header in forms. Leave a trailing slash.	SYS
SCR_HEADER_TEXT_COLOUR	Colour of text in header toolbars on forms	SYS
SEC_GROUP_OR_BASEDAT	Security - Lock Monitor, display Group or Based at	SYS
SEND_CAN_WITHOUT_BOOKING	Allow CAN message to be sent without Booking Ref	SYS
SEND_INTERFACE_FAIL_EMAIL	Send email for interface errors	COS
SEND_LINE_ITEM_TO_LOTS	Send Line Item To LOTS. Y - send both Order Line (D) and Item (S) records. N - Checks for Items and, if there are any, sends Item (S) records, else Order Line (D) records.	SYS
SEND_MANF_TO_SUPP	Indicates if the supplier manifest report will be automatically generated when a trip is accepted for the cost centre of the trip being collected.	COS
SEND_MANF_TO_SUPP	Indicates if the supplier manifest report will be automatically generated when a trip is accepted for the cost centre of the trip being collected.	CUS
SEND_MIL_MESSAGES	Send Tracking Milestone Messages	CUS
SEND_PALLET_ID_XML	Send Pallet ID tag in xml	COS
SEND_SCP_MESSAGES	Send Supplier Collection Messages	CUS
SEND_SMS_EMAIL	Controls whether a SMS or an e-mail may be sent to the recipient of the order being delivered on the trip (Y/N).	COS
SEND_SMS_EMAIL_OLD	Controls whether a SMS or an e-mail may be sent to the recipient of the order being delivered on the trip (Y/N).	COS
SEND_TO_ISOTRAK	Send to ISOTRAK - ALL or NONE.	SYS
SERVICES	Controls if service payments are generated	COS
SESSION_DEFAULT_LOAD_RATE	Session Default Load rate	COS
SESSION_DEFAULT_UNLOAD_RATE	Session Default Unload rate	COS
SET_FAST_ORD_WINDOWS	Call fast order windows in Import	SYS
SET_MICROLISE_SLOTS	Determines if the delivery slot times are sent to Microlise instead of the planned delivery times.	SYS
SET_TRUNKS_ACCEPTED	Are Trunk trips automatically set to ACCEPTED status?	SYS
SFTP_LOG_LEVEL	SFTP Log level - numeric 0-3	SYS
SHA_EXCLUDE_AUDIT	Activity types that will be excluded from writing audit log records when they are activated.	SYS
SHIFT_ADDITIONAL_HOURS	Threshold for charging additional shift hours	COS
SHIFT_DISTANCE	Shift Distance	COS



Parameter	Description	
SHIPMENT_NO_QTY_RATING	Indicates if a shipment can be rated without quantities	CO3
SHIPMENT_VOLUME	Maximum shipment volume	SYS
SHIPMENT_WEIGHT	Maximum shipment weight	SYS
SHOW_CAPPED_TONNAGE	Display Capped Tonnage Details	SYS
SHOW_CARRIER_NAME	Is carrier name shown on Planning screen?	SYS
SHOW_CONTACT	Show contact name and number on labels.	CO3
SHOW_FULL_ADDRESS	Show full delivery address on labels.	CO3
SHOW_SCANNED_ITEMS_BTN	Display Scanned Items Update Button	SYS
SLOT_DFLT_TRAILER_TYPE	Default Trailer Type for Slots	SYS
SLOT_EXP_DIR	Slot Export - FTP to directory	SYS
SLOT_EXP_IP	Slot Export - FTP to IP address	SYS
SLOT_EXP_LOGIN	Slot Export - FTP using login	SYS
SLOT_EXP_PORT	Slot Export - FTP to Port	SYS
SLOT_INC_ADD_CORE_TYPES	Set to Y if Slot are to be defined as type CORE or ADDITIONAL	SYS
SMA_ALLOW_CREATE_ORDERS	Allow orders to be created	SYS
SMA_FTP_DESTINATION_DIRECTORY	Directory for FTP of Smartphone Files	SYS
SMA_FTP_DESTINATION_IP_ADDRESS	IP for FTP of Smartphone Files	SYS
SMA_FTP_DESTINATION_PASSWORD	Password for FTP of Smartphone Files	SYS
SMA_FTP_DESTINATION_PORT	Port for FTP of Smartphone Files	SYS
SMA_FTP_DESTINATION_USERNAME	Username for FTP of Smartphone Files	SYS
SMA_INBOUND_ARCH	Path for Smartphone XML archiving	SYS
SMA_INBOUND_FAIL	Path for Smartphone XML failure	SYS
SMA_INBOUND_IDENTIFIER	Pattern for SMA Trip inbound XML	SYS
SMA_INBOUND_LISTING_NAME	Filename for list of files in directory for SMA XML trip inbound	SYS
SMA_INBOUND_PATH	Path for yet to be processed XML files from Smartphone	SYS
SMA_LISTING_SCRIPT_NAME	Script name for SMA XML Trip inbound	SYS
SMA_OUTBOUND_ARCH	Path for archiving outbound Smartphone XML interface	SYS
SMA_OUTBOUND_FAIL	Path for failing outbound Smartphone XML interface	SYS
SMA_OUTBOUND_PATH	Path for outbound Smartphone XML interface	SYS
SMA_OWNING_DEPOT	Indicates if the Smartphone file is sent with Database or owing depot in the name	SYS
SMA_RESOURCE_UPDATE	Update resources on receipt of Smartphone message	CO3
SMA_SEND_ACCEPTED	Send ACCEPTED message to SMARTPHONE	SYS
SMA_SET_TO_COMP_CONF	Update Trip Status once Smartphone has provided all quantities and times	SYS
SMA_TO_DELIVER_IS_DELIVERED	Auto-Default the TO_DELIVER quantity from the DELIVERED quantity	CO3
SMS_AUDITING	Will records be audited in ADM_LOG for the SMS_EMAIL messages (Y/N)?	SYS
SMS_COL_DEL_BOTH	Send SMS for delivery/collection orders or both? (COL, DEL, BOTH)	CO3
SMS_GATEWAY_PWD	SMS Gateway Password	SYS
SMS_GATEWAY_URL	SMS Gateway URL	SYS
SMS_GATEWAY_USER	SMS Gateway Username	SYS
SMS_LANDLINE_EXCLUSION	Will SMS be excluded for landlines? (Y/N)	SYS
SMS_LOC_TYPES	Limit SMS and EMAIL Notifications to this list of location types only. If blank messages are sent for all stops	CO3
SMS_MULTI_MSG	Send multiple SMS message for each trip stop (Y/N)	CO3
SMS_SENDER_NUM	SMS Sender number to stop replies	SYS
SMS_SERVICE_BOX	Stores the e-mail address of the SMS service box.	SYS



Parameter	Description	
SMS_SERVICE_BOX_OLD	Stores the e-mail address of the SMS service box.	SYS
SMTP_ORDER_SENDER	Order Email Sender address	SCH
SMTP_ORD_CONF_SENDER	Ord Conf Email Sender Address	CO
SMTP_ORD_CONF_SENDERXX	Ord Conf Email Sender Address	CO
SMTP_PASSWORD	SMTP password	SYS
SMTP_PORT_NUMBER	SMTP Port Number	SYS
SMTP_PRIMARY	Primary Mail Server	SYS
SMTP_SECONDARY	Secondary Mail Server	SYS
SMTP_SENDER	Email Sender address	SYS
SMTP_SMS_PRIMARY	Primary mail server for SMS.	SYS
SMTP_SMS_SECONDARY	Secondary mail server for SMS.	SYS
SMTP_SMS_SENDER	Sender address for SMS.	SYS
SMTP_TRIP_SENDER	Trip Email Sender address	CO
SMTP_USER	SMTP Username	SYS
SOUTHERN_MANIFEST	Depot Linked to Southern Manifests	SYS
STOP_PID	LOTS - is STOP_PID included in the extract	SYS
SUBMIT_CARGOWISE_HEADER	Enter the number of minutes from FTP support files complete status to send header file?	SYS
SUGGEST_TRIP	Suggest an appropriate trip for an order	CO
SUPPLIER_MANF	Indicates the name of the supplier manifest report to be automatically generated when a trip is accepted.	CO
SVC_USE_SERVICE_TYPES	Controls whether Service types are to be used which includes the use of transaction, manual, late and urgent order charging.	SYS
T2A_ASSET_ARRIVED_OFFSET_DAYS	A number of offset days from the current date to select orders that have arrived at the depot for T2A Forward Items.	SYS
T2A_ASSET_DUE_OFFSET_DAYS	A number of offset days from the current date to select orders that are due arrive at the depot for T2A Forward Items.	SYS
TAG_TO_ASSET_SCANNING	Allow scanning and recording of Tags	SYS
TA_EMAIL_SUBJECT	Email subject for automatically e-mailing manifest	CO
TA_EMAIL_SUBJECT	Trip accept. Email subject.	SYS
TA_EMAIL_TEXT	Trip accept. Email message	SYS
TA_EMAIL_TEXT	Email text for automatically e-mailing manifest	CO
TA_FILE_NAME	Trip accept. Name of output file.	SYS
TA_FTP_DIRECTORY	Trip accept. FTP report to upload directory.	SYS
TA_FTP_IP_ADDRESS	Trip accept. FTP report to IP address.	SYS
TA_FTP_PASS	Trip accept. FTP report using password.	SYS
TA_FTP_PORT	Trip accept. FTP port.	SYS
TA_FTP_USER	Trip accept. FTP report using username.	SYS
TA_PDF_TO_TIFF1	Trip accept. Convert pdf to tiff.	SYS
TA_PDF_TO_TIFF2	Trip accept. Convert pdf to tiff.	SYS
TA_PDF_TO_TIFF3	Trip accept. Convert pdf to tiff stage 3.	CO
TA_PDF_TO_TIFF3	Trip accept. Convert pdf to tiff. Rotation for landscape	SYS
TA_REPORT_NAME	Trip accept. Name of report to be run. Please include the .rep extension.	CO
TA_REPORT_NAME	Trip accept. Name of report to be run. Please include the .rep extension.	SYS
TA_SUB_FROM	Trip accept. Sub file from	CO
TA_SUB_FROM	Indicates Zetafax value in .sub file in FROM:	CO
TA_SUB_FROM	Trip accept. Sub file from	SYS
TA_SUB_ORGANISATION	Trip accept. Sub file organisation	SYS
TA_SUB_PRIORITY	Trip accept. Sub file priority	SYS
TA_SUB_USER	Trip accept. Sub file user	CO



Parameter	Description	
TA_SUB_USER	Trip accept. Sub file user	SYS
TA_SUB_USER	Indicates Zetafax value in .sub file in USER:	COS
TDL_GEN_ITEMS	Allow order items to be generated from lines	SYS
TDL_INBOUND_ARCH	Path for TDL XML archiving	SYS
TDL_INBOUND_IDENTIFIER	Pattern for TDL Inbound XML	SYS
TDL_INBOUND_PATH	Path for yet to be processed XML files from TDL	SYS
TDL_ITEM_IN_PORTAL_FORMAT	Generate item identifier in portal format in order entry	SYS
TEND_EMAIL	Different format for Tender invitation	SYS
TEST	Controls whether certain testing functions are enabled - Y or N	SYS
TIMES_LOADING_TIME	Default Loading Time used in Slots import when recalculating times	SYS
TIME_ZONE_ACTIVE	Time Zone Active	SYS
TMS_AUTO_DEFAULT_RESOURCE	Automatically default the Resource - Smartphone	COS
TMS_OTBOUND_SO_REF	Controls the outbound format for SO_REF in LOTSC	CUS
TOK_CNAME	Defines the Tokairo Customer Name.	CUS
TOK_CUSTOMERS	A comma-delimited list of customers to interface with Tokairo.	SYS
TOK_FIELD	Defines the Tokairo field name.	CUS
TOK_OUTBOUND_ARCHIVE	Filepath for Tokairo Daily Extract archive	SYS
TOK_OUTBOUND_PATH	Filepath for Tokairo Daily Extract	SYS
TOK_POD_AVAIL	Is Tokairo being used to view POD documents - Y or N.	SYS
TOK_SRCH_PAGE	Defines the Tokairo search page.	SYS
TOK_URL_PREFIX	Defines the Tokairo URL prefix.	SYS
TOK_VIRDIR	Defines the Tokairo virtual directory.	CUS
TOMTOM_CHECK_DEPOT	Check the depot to control data sent to depot	SYS
TOMTOM_DRIP_FEED	Are stops sent to Webfleet by drip feed process	SYS
TOMTOM_ORDER_TYPES	Are WEBFLEET order types derived	SYS
TOMTOM_TIMES_ONLY	Do actual times on SU and CL set trip status	SYS
TRANSPORT_MODE	Are Customer Transport Mode Factors Required	COS
TRIP_ALWAYS_SHOW_EMERGENCY_ORDERS	Emergency Deliveries are always displayed regardless of filter criterion	SYS
TRIP_BRIEF_MAINTENANCE	Enable the Trailer Type, Rated Cost and Message Configuration to be maintained in Carrier Selection for trip planning (Y/N).	COS
TRIP_CHARGING_METHOD	Determines whether the calculation for the costs includes the trailer type of the trip: F is Fixed and includes the trailer type.	COS
TRIP_HAZARD_DISPLAYED	Show the Trip hazardous Totals or not.	SYS
TRIP_HAZARD_LEVEL1_CODE	The colour code of the hazardous weight level 1.	SYS
TRIP_HAZARD_LEVEL1_FROM	The lower value in the range of the hazardous weight level 1.	SYS
TRIP_HAZARD_LEVEL1_TO	The upper value in the range of the hazardous weight level 1.	SYS
TRIP_HAZARD_LEVEL2_CODE	The colour code of the hazardous weight level 2.	SYS
TRIP_HAZARD_LEVEL2_FROM	The lower value in the range of the hazardous weight level 2.	SYS
TRIP_HAZARD_LEVEL2_TO	The upper value in the range of the hazardous weight level 2.	SYS
TRIP_HAZARD_LEVEL3_CODE	The colour code of the hazardous weight level 3.	SYS
TRIP_HAZARD_LEVEL3_FROM	The lower value in the range of the hazardous weight level 3.	SYS
TRIP_HAZARD_LEVEL3_TO	The upper value in the range of the hazardous weight level 3.	SYS
TRIP_HAZARD_PRODUCTS		SYS



Parameter	Description	
	List the descriptions of the product types considered to be hazardous using a comma as a delimiter.	
TRIP_LABELS	Indicates the name of the report to be run from the Print Labels menu option in the trip tree in the Planning screen.	CO
TRIP_ORDER_XSD_VERS	Version of TRIP XSD being used.	SYS
TRIP_ORD_LATE_FORMAT_MASK	Display the format of the late available and late delivery columns as time only (TIME) or date and time (DATETIME).	SYS
TRIP_OVERVIEW_CURRENT_TYRES	Use the current quantity of tyres in the Trip Waterfall screen (Y/N)	SYS
TRIP_PREVENT_PARCEL_CARRIER_ASSIGNMENT	Controls the manual assignment and cross-docking of transport orders to trips for parcels (Y to disable or N to enable).	CO
TRIP_SHEET	Trip Sheet Report	CO
TRIP_TRAMPS_ON_WATERFALL	Allow tramping trips to be shown in waterfall form by date not schedule	SYS
TRIP_VALIDATE_PARCEL_ORDER_ASSIGNMENT	Controls validation of parcel orders to trips for parcel carriers (Y to disable or N to enable).	CO
TRLR_TYPE_RATE	Are trailer types included when estimating cost?	CO
TRM_3PL_SCHEDULE_NO_DROP	Enable orders without a drop number for the run to be pre-planned for Paragon (Y/N)	SYS
TRM_ACTION_MITIGATION	Order Reason Actions requiring Mitigation	SYS
TRM_ACTIVITY_QTY	Use Activity Quantity to determine when to create DEP control record	CO
TRM_ACT_PMTS_DEL_ORD_AT_CONF	Control whether Order payments should be updated, and Orders set to DELIVERED when Trip is set to confirmed	SYS
TRM_ADD_EDIT_ITEMS	Trip manipulation - display additional edit items.	SYS
TRM_ALLOW_REJECTIONS	Allow trips to be rejected when they are not tendered (Y/N)?	SYS
TRM_APPLY_DRIVER_BREAK_RULES	Switches Driver Breaks on or off - Y or N	SYS
TRM_APPLY_POD_AFTER_ACTUALS	Apply the POD after the all actuals button is pressed (IIB)	SYS
TRM_AUTO_DEL_TRIP_UNSCHE	Automatically delete trips when the last order is unscheduled from it	CO
TRM_AUTO_SET_ACCEPTED	Auto Set trip to accepted once all resources allocated	CO
TRM_BAXTER_ROUTES	Used to control when the process to populate trunk and radial routes is called	CO
TRM_BOL_PREFIX	Prefix that will be added to BOL when created in MTS.	CO
TRM_BOL_SUFFIX	Suffix that will be added to BOL when created in MTS.	CO
TRM_CANCEL_EMPTY_ORDER	Remove orders from trip going to Accepted if there are no items	CO
TRM_CARRIER_AUDIT	Controls whether audit records are written for Carrier CHANGES	CO
TRM_CHECK_CREW	Indicates if the Check_Crew functionality should be run.	CO
TRM_CHECK_LIMITS	Controls level at which Weight, RPE and Volume limits are checked - BY_STOP or NULL	SYS
TRM_CHK_DRIVER_CARRIER	Use carrier hubs if driver hubs not set	CO
TRM_CL_DFLT_fixed_time	Default Close Down time (minutes)	SYS
TRM_COMPLETED_SETTINGS	Indicates if CC/Customer Completed settings are in use	CO
TRM_CONSOLIDATE_STOPS	Allow consolidation of order on stops if time windows do not overlap	SYS
TRM_CONSOL_ORDER_AFTER_XDOCK	Consolidate the available time windows for a collected order against the orders being loaded for delivery (Y/N)	SYS



Parameter	Description	
TRM_CROSSDOCK_TIME	Time offset for delivery into crossdock location	CO3
TRM_DEBRIEF_SCREEN_TIME_VARIANCE_DISPLAYED	Is the Time Variance field displayed and updateable in the Trip Debrief screen.	SYS
TRM_DEFAULT_DRIVER	Default Driver ID	CO3
TRM_DEFAULT_TRACTOR	Default Tractor ID	CO3
TRM_DEPOT_SCANS	Are trunk trip scans checked	SYS
TRM_DESP_FOR_DEL	Maintain the Actual Despatched Quantity for a Delivery Trip in Trip Debrief (Y/N).	CO3
TRM_DFLT_DRV_BREAK_MINS	Default Driver Break (minutes)	SYS
TRM_DFLT_MAX_DRV_HRS_WO_BREAK	Default maximum drive hours without break	SYS
TRM_DFLT_MAX_DRV_HRS_WO_STOPOVER	Default maximum drive hours without stopover.	SYS
TRM_DFLT_MAX_WRK_HRS_WO_BREAK	Default maximum work hours without break	SYS
TRM_DFLT_MAX_WRK_HRS_WO_STOPOVER	Default maximum work hours without stopover.	SYS
TRM_DFLT_STOPOVER_BREAK_MINS	Default stopover duration (minutes).	SYS
TRM_DFLT_WRK_BREAK_MINS	Default work break duration (minutes)	SYS
TRM_DISPLAY_ERROR_MULTI_TRIP	Display Errors when changing multiple trips status	CO3
TRM_DISP_ISOTRAK_OR_EFX	Controls whether the Isotrak Ref or EFX Ref is displayed in the TRIPSUM form - ISOTRAK or EFX	SYS
TRM_DISP_OMS_OR_CUST_REF_OR_BOOK_OR_CONT_NO	Display OMS, Customer Ref, Booking Ref or Container No - OMS_REF, CUST_REF, CONT_NO or BOOKING_REF.	SYS
TRM_DISP_REV_COLDEL	Display Revenue on collection or delivery trip	CO3
TRM_DISP_RPE_DU_OR_WEIGHT	Controls whether RPE Qty, DU Qty or Total Weight is displayed in the TRIPSUM form - RPE, DU or WEIGHT.	SYS
TRM_DISP_SCHED_ALL	Trip manipulation - display schedule all check box.	SYS
TRM_DISP_VOL_OR_CASES	Controls whether Volume or Cases is displayed in Unscheduled Orders in TRIPSUM forms - VOLUME or CASES	SYS
TRM_DISTRIBUTE_MAX_ORD_COST	Indicates if the cost centre will DISTRIBUTE revenue charges	CO3
TRM_DO_NOT_UPDATE_ORD_DEL	Leave the order delivery type when the trip delivery type is different	CO3
TRM_DRIVER_HUB	Drivers are aligned to a Hub Location	SYS
TRM_DRIVER_RQD_FOR_ENROUTE_OR_ACC	Is a Driver required before a Trip can be set to EN_ROUTE or ACCEPTED	CO3
TRM_EARLIEST_STOP_WINDOW	Toggle (Y/N) to specify whether consolidation uses the earliest stop	SYS
TRM_ENFORCE_CARRIER_RULES	Enforce Carrier Hub Location Rules	CO3
TRM_ENFORCE_TRIP_RECALC	Enforce Trip Recalculation - YES or NO	SYS
TRM_EXCL_REG_AUTO	Planning Regions to be excluded from Auto Scheduling	CO3
TRM_EXCL_TIME_VALIDATION	Indicates if the available time of an order is not compared to the cut-off time for TRUNK or LINEHAUL routes in the network scheduling engine (Y/N).	SYS
TRM_FIXED_TRIP_STATUS	Determines status of trips created via Fixed Schedules. P for PLANNED or A for ACCEPTED.	SYS
TRM_HIGHLIGHT_OVERDUE_FINISH	Trip Status used in Trip Overview screen to highlight overdue finish time	SYS
TRM_HIGHLIGHT_OVERDUE_START	Trip Status used in Trip Overview screen to highlight overdue start time	SYS
TRM_IGNORE_DUP_LOC_CHECK	Dunelm orders from a supplier in Scotland to a store in Scotland need to visit the trailer swap location twice so ignore standard checks in TRM	SYS
TRM_INCL_TRUNK	Are trunk trips to be validated	SYS
TRM_INC_BASED_AT_LOC_TRIPS	Allows viewing of other depots transiting	SYS
TRM_LFS_PRINT_TRIP_POD_POC		SYS



Parameter	Description	
	Display LFS Trip Sheet POD POC report menu option (Y/N)?	
TRM_LOAD_DFLT_fixed_time	Default Loading Time (minutes)	SYS
TRM_LOAD_dflt_mins_per_rpe	Default loading rate per RPE (minutes)	SYS
TRM_LOAD_dflt_mins_per_weight	Default Loading rate per Weight (minutes)	SYS
TRM_LOC_RADIAL_ROUTES	Indicates if a radial route that is stored for the location will be used in the scheduling engine instead of the location zones (Y/N).	SYS
TRM_MANIFEST_DATES	Controls if the manifest is run based on dates	COS
TRM_MAX_DRIVING_HOURS	Maximum Driving Hours	SYS
TRM_MAX_ORD_COST	Indicates if the cost centre will base revenue charges on the Maximum at a single stop	COS
TRM_MAX_SHIFT_HOURS	Maximum Shift Hours	SYS
TRM_MAX_STOP_COST	Indicates if the cost centre will base cost charges on the Maximum at a single stop	COS
TRM_MAX_STOP_REVENUE	Indicates if the cost centre will base revenue charges on the Maximum at a single stop.	COS
TRM_MAX_WAIT_TIME	Maximum waiting time at Location (minutes)	COS
TRM_MERGE_END_OR_EXISTING_STOPS	Method-assigning orders to resulting trip in merge trips. Values: END or EXISTING. END adds orders to end. EXISTING adds orders to 1st available stop.	SYS
TRM_MIC_DRIVER	Are driver minutes updated from Microlise debrief	COS
TRM_MODIFY_SCHED	Allow the stop times of the delivery trip to be updated to match the new delivery times of the scheduled order (Y/N).	COS
TRM_MOVE_ITEM_TO_DESP_BAY	Move an item from the grid to the despatch bay when added to the order on the trip or its order is assigned to the trip (Y/N)	SYS
TRM_NETWORK_STOPS	Are trunk trip times set by the network table	COS
TRM_NEW_TRIP_STATUS_CHECKS	Control new restrictions on trip status change.	SYS
TRM_NLP_SUMMARY	Request a summary by country in the NLP distance and time calculations(Y/N)	COS
TRM_NLP_SUMMARY	Request a summary by country in the NLP distance and time calculations(Y/N)	COS
TRM_NON_STD_INSTRUCTIONS	Calculate Planning Instructions on Carrier Trip Form	COS
TRM_NO_STOP_DELETE	Do not delete stops	COS
TRM_NO_TIME_VALIDATION	Trip prefix to prevent validation	COS
TRM_ODO_DISTANCE_LIMIT	Limit used to validate difference between odo start and end entries in debrief areas of Trip Forms	SYS
TRM_OFFSET_PUBLIC_HOLIDAY	Indicates if the order time windows and the scheduling engine will be offset for the public holiday at the country, depot or route level (Y/N).	SYS
TRM_ORD_OVERVIEW	Include Orders in Trip Overview screen	COS
TRM_ORD_SCHED_FROM	Number of days back for schedule range	COS
TRM_ORD_SCHED_FROM_PLANNING	Number of days back for schedule range in Planning screen	SYS
TRM_ORD_SCHED_SEARCH	Maximum number of days for schedule range	COS
TRM_ORD_SCHED_SEARCH_PLANNING	Maximum number of days for schedule range in Planning screen	SYS
TRM_ORD_SCHED_TO	Number of days forward for schedule range	COS
TRM_ORD_SCHED_TO_PLANNING	Number of days forward for schedule range in Planning screen	SYS
TRM_OVERVIEW_AMBER_TIME	Time allowed before start and finish times are amber in TRIP OVERVIEW	SYS
TRM_OVERVIEW_RED_TIME	Time allowed before start and finish times are red in TRIP OVERVIEW	SYS
TRM_PLAN_ALL_RET_ORDERS	Plan all RET orders	COS



Parameter	Description	
TRM_PLAN_INVALID	Are un-manifested orders set to invalid	SYSS
TRM_PREVENT_ALL_DEBRIEF	Prevent setting of actuals in trip debrief	SYSS
TRM_PREVENT_CONSOL_ACROSS_STOPS	Stop orders being added to shipments when not on same stops	COSS
TRM_PREVENT_ORD_ON_COMP_STOP	Prevent Orders Being Planned on Completed stops	SYSS
TRM_PROSPERO_ADV_DAYS	Advance Scheduling days for Prospero	SYSS
TRM_PROTECT_SHUNTS	Protect the times from the order windows for the trip stops for shunt trips for collections (Y/N)	SYSS
TRM_RECALC_ELAPSED_TIME	Always recalculate elapsed time on trip	COSS
TRM_RETAIN_CARRIER_NEW_SCHED	It is to retain a carrier when the schedule of the trip is updated. Otherwise, the carrier is reset to the carrier for the owning depot.	COSS
TRM_RETAIN_EMPTY_STOPS	Retain empty stops when validating the trip.	COSS
TRM_RETAIN_MTM	Retain MTM cost when set to Planned	SYSS
TRM_RETAIN_ORD_STATUS_TRIP_COMPLETE	Retain the current order status if trip status is set to COMPLETED (Y/N)	COSS
TRM_RETAIN_PACK_DATA	Retain Pack Data either via Paragon or advise user to retain or delete pack data if manually unscheduling order.	COSS
TRM_ROUND_RPE_AT_STOP	Round RPE at unload stop	SYSS
TRM_SCHEDULE_BY_DEL	Controls if orders are manually scheduled onto trips by del time	SYSS
TRM_SEND_PLUTO_ACTUALS	Actuals process for PLUTO	COSS
TRM_SEND_PRE_DELIVERY_MSG	Activates email and SMS functionality	COSS
TRM_SET_ACTUALS_AFTER_ENROUTE	Should Actuals (arrive/depart) be set for Trip stop 1 when trip is set to En-Route - Y or N	COSS
TRM_SET_DESP_AFTER_ENROUTE	Should the actual despatched values for an order be set when the trip status is set to EN-ROUTE (Y to enable or N to disable).	COSS
TRM_SET_NEW_STOP_TIMES	Trip prefix to set stop times based on trip duration	COSS
TRM_SET_OWNING_DEPOT	Priority for assigning owning depot to a trip	COSS
TRM_SET_TO_COMPLETED	Should trip be auto set to Completed. Values are N, ACTUAL (after actuals have been applied), POC/POD (when POC and POD applied to all Orders).	COSS
TRM_SET_TO_COMP_AFTER_TIMES	Are trips set to completed when stop actuals have been set?	SYSS
TRM_SET_TO_CONFIRMED	Should trip be auto set to Confirmed. Values are N, ACTUAL (after actuals have been applied), POC/POD (when POC and POD applied to all Orders).	SYSS
TRM_SET_TO_ENROUTE_AFTER_ACTUALS	Should trip be set to En-Route after first order has been collected - Y or N	COSS
TRM_SHIFT_TIMES_FOR_TRIP	Use Shift Times For Start And End Times Of Trip	SYSS
TRM_SHOW_LATE_BUTTON	Is the Show Late Reasons Button visible.	SYSS
TRM_SHOW_TIME_DEBRIEF_BTNS	Show time debrief buttons in trip debrief	SYSS
TRM_SHOW_TRIP_EXPORT_BTN	Show Export Button in TRIP screens. Specifically for Road Ops Report	SYSS
TRM_SOURCE_SYSTEM	Highlight the trip details when it contains an order without an OPEN status in the WMS source system (Y/N)	SYSS
TRM_STACK_DEBRIEF	Trip Stack Debrief	COSS
TRM_STATUS_FOR_CONSOLIDATION	The trip status that controls the consolidation by customer or customer group, enter BOTH for ACCEPTED and PLANNED	SYSS
TRM_STOP_TIMES_FROM_ORDS	Will the trip stop times be inherited from the delivery time window of the order? (Y/N)	CUS
TRM_STORE_TRIP_MOVES	Determines whether audit of old and new trips is stored against orders	COSS



Parameter	Description	
TRM_SU_DFLT_fixed_time	Default Start Up time (minutes)	SYS
TRM_SVC_TYPE	Is SVC_TYPE Editable on TRIP forms?	SYS
TRM_TEMP_DEBRIEF	Display temperature on Trip debrief	SYS
TRM_TRACTOR_RQD_FOR_ENROUTE_OR_ACC	Is a Tractor (Vehicle) required before a Trip can be set to EN_ROUTE or ACCEPTED	COS
TRM_TRAILER_RQD_FOR_ENROUTE_OR_ACC	Is a Trailer Id required on every stop before a Trip can be set to EN_ROUTE or ACCEPTED	COS
TRM_TRANSPORT_MODE_REQD	Is the transport mode on the trip screens a required field	COS
TRM_TREE_FORMAT	Determines trip tree display format	COS
TRM_TREE_ROUTE	Determines whether Route code is displayed in trip tree	COS
TRM_TRIP_STATUSES	List of Trip Statuses to control which trips displayed in Tripdtl/Trip Debrief form.	SYS
TRM_TRUNK_TIME	Time in minutes for assessing Trunk Trips	COS
TRM_UNLOAD_DFLT_fixed_time	Default unloading time (minutes)	SYS
TRM_UNLOAD_dflt_mins_per_rpe	Default unloading rate per RPE (minutes)	SYS
TRM_UNLOAD_dflt_mins_per_weight	Default Unloading rate per RPE (minutes)	SYS
TRM_UNSCHEDULE_TO_CANCEL	Controls if orders are Unscheduled when a cancellation is received	SYS
TRM_UPDATE_ALL_ACTUALS	When a line actual is debriefed all actuals are set	COS
TRM_USE_ACTUALS_FOR_STOP_TIMES	Use Actual Times at stops to calculate times for next stop	SYS
TRM_USE_MAX_RPE_OF_LARG_TRAILER	Controls whether MTS uses Max RPE of Largest Trailer Type when adding Orders to Trips - Y or N (N will use Current Trailer)	SYS
TRM_VALIDATE_STOP_TIMES	Show Validation messages on stop times and prevent the user from going to accepted (Y/N)	SYS
TRM_VALIDIDATE_DU_TEMP	Validate Du temp by product and DU	COS
TRM_VAL_CAR_VESSEL	Trip manipulation - validate carrier after vessel has been allocated.	SYS
TRM_WASTE_SITE	Amend TO_LOC to a waste site in order well	COS
TRM_WEIGHTED_AVE_FILL_ACCEPT_PCEN	Defines the acceptable percentage for trip weighted average fill	SYS
TRM_WEIGHTED_AVE_FILL_MIN_PCEN	Defines the minimum required percentage for trip weighted average fill	SYS
TRM_WMS_STATUS	Controls if WMS status is calculated and if WMS status fields displayed in Trip forms.	COS
TRM_XDOCK_VALIDATION	Different Validation for the Cross dock process	COS
TRM_XDOCK_VIA_ROUTE	Display additional route information when selecting trip for XDOCK orders (Y/N)	SYS
TRP_RED_TRUCK_ERRORS	Indicates if the truck icon is red to indicate an error	SYS
TRP_SEND_ENABLE_MSG	Which enabling message is to be sent by Trip form	SYS
TRP_SEND_WAREHOUSE_LOAD	Include Warehouse Loading Time in the outbound XML flow.	COS
TRP_STACK_DEBRIEF	Trip Stack Debrief	COS
TRUNK_LOAD	Time (minutes) to load an order on a trunk trip	SYS
TRUNK_UNLOAD	Time (minutes) to unload an order on a trunk trip	SYS
UKMAIL_ADD_INFO_LABEL	Additional information on UKMail Label	COS
UKMAIL_USE_CUST_REF_ON_LABEL	Controls if customer ref is displayed on UKMAIL label	CUS
UNISON_ORDER_INT_TYPE	EIH Interface Type (UNISON ORDER)	SYS
UNI_DEFAULT_DU_TYPE	Default DU Type for Orders created via the UNISON interface.	SYS
UNI_ENABLED	To enable the inbound and outbound file processing on this DB	SYS
UNI_FTP_DESTINATION_DIRECTORY	Directory for FTP of Unilever Files	SYS



Parameter	Description	
UNI_FTP_DESTINATION_IP_ADDRESS	IP for FTP of Unilever Files	SYS
UNI_FTP_DESTINATION_PASSWORD	Password for FTP of Unilever Files	SYS
UNI_FTP_DESTINATION_PORT	Port for FTP of Unilever Files	SYS
UNI_FTP_DESTINATION_USERNAME	Username for FTP of Unilever Files	SYS
UNI_INBOUND_ARCH	Path for processed XML files that have successfully completed processing, see: int_po_inbound_header (Unilever)	SYS
UNI_INBOUND_FAIL	Path for processed XML files that have failed processing for reasons described against int_po_inbound_header (Unilever)	SYS
UNI_INBOUND_PATH	Path for yet to be processed XML files (Unilever)	SYS
UNI_LOCATION	Location for Unilever	SYS
UNI_OUTBOUND_ARCH	Path for processed XML files for Unilever	SYS
UNI_OUTBOUND_FAIL	Path for processed XML files for Unilever that have failed processing	SYS
UNI_OUTBOUND_IDENTIFIER	Unilever outbound file identifier	SYS
UNI_OUTBOUND_PATH	Path for yet to be processed XML files for Unilever	SYS
UNSCHED_ORDERS_DEL_DAYS	Unscheduled orders on schedules older than this value will be deleted	SYS
UPDATE_DIR	client Server Update directory	SYS
UPDATE_IP_ADDR	Client Server Update IP Address	SYS
UPDATE_IP_ADDR_CGEY	CGEY Client Server IP Address	SYS
UPDATE_ORDERS_TO_TRIP	Update Order Windows to match selected trip	CO
UPDATE_ORDER_TIMES_TO_TRIP	Enable the current orders to have their time windows updated to match the stop time windows in the 'Confirm Update/Add' process (Y/N)	CO
UPDATE_PASSWORD	Client Server Update Password	SYS
UPDATE_TO_DELIVER	update the To deliver quantity with the Ordered quantity for New order Items	SYS
UPDATE_USER	Client Server Update User	SYS
UPD_CUST_DATES	Default part Number	CUS
UPGRADE_PASSWORD	Client Server Upgrade Password	SYS
UPGRADE_USER	Client Server Upgrade Username	SYS
UPPERCASE_ASSET_ID	Asset id to be stored in upper case	SYS
URGENT_ORDER	Controls if Urgent Notification emails are sent to planners	CO
URGENT_ORD_DELIVERY	Controls which delivery types trigger an urgent notification	CO
URGENT_ORD_RECIPIENT	Controls who receives an urgent notification	CO
USE_CHILD_LOCATIONS	Use any child locations in preference to the master locations of an order in the requested reports? (Y/Y)	CO
USE_ORDER_ADDRESSEE	Will the addressee name be used for the order? (Y/N)	CO
USE_PACK_QUANTITY	Use the current quantity of tyres in the Trip Waterfall screen (Y/N)	SYS
USE_PALLET_ID_XML	Use Pallet ID instead of item identifier in XML Outbound files	CO
USE_SECURITY_PROFILES	Use Security Profiles for users	SYS
USE_SMS_GATEWAY	Use SMS Gateway for SMS message sending	SYS
USE_XML_ORDER_SUB_REFS	Print order sub refs on outbound XML	CO
USE_XML_ORDER_SUB_REFS	Print order sub-references in the outbound XML file? (Y/N)	CO
UTL_IMPORT_IGNORE_INVALID_OPERATION	The import process of files will suppress the auditing of messages when a file does not exist on the server to overwrite (Y/N)	SYS
VALIDATE_LOCATION_ON_CLOSE	Validate address details if the close button is pressed within locations screen (Y/N)?	SYS



Parameter	Description	
VALIDATE_MASTER_LOC	Validate the collection and delivery location of the order against the decoded master locations (Y/N)	CO
VB_UPLOAD_APP_VERSION	Version number of the PC MTS Upload/Import Application written in Visual Basic	SYS
WARN_MISSING_PO	Warn if No PO Allocated to a trip when status or carrier changed	CAR
WARN_OUTSTANDING4933	Warn of unmatched 4933 orders on trip status change	CUS
WATERFALL_UPDATES	control updates on the waterfall screen	SYS
WCS_441_CHECK_DAYS	Set a number of days in which to assess the prior loading messages for WCS.	SYS
WCS_CALC_ITEM_WGT_VOL	Calculate the weight and volume for the DU in the 804 scan (Y/N).	CO
WCS_CALC_ITEM_WGT_VOL	Calculate the weight and volume for the DU in the 804 scan (Y/N).	CUS
WCS_CLEARDOWN_DAYS	Number of days after which WCS control records will be cancelled.	SYS
WCS_COLLECTION_PREADVICE	Do we call collection pre-advice	NO
WCS_COMBINED_ADD_LOAD	WCS add items and loading into a single scan	SYS
WCS_DEFAULT_AGENT	Default agent for WCS messages	SYS
WCS_DUAL_INSTANCE	Dual Instance WCS....***DUNELM ONLY***	SYS
WCS_ENABLED	Is the WCS system enabled?	SYS
WCS_MIN_ITEM_LENGTH	Min length of WCS_ITEM to check for match in CTMS	SYS
WCS_MULTI_DEPOTS	Pre-advice WCS when depot is different	SYS
WCS_OLD_404_DAYS	Number of days to allow old 404 messages to be sent to WCS	SYS
WCS_ORD_BUILD_ENABLED	Y to enable WCS Re-advice resend of Orders Overnight Processing	SYS
WCS_RETAIN_EMPTY_LINES	Retain any empty order lines that have been created when their items have been deleted during the order confirmation process? (Y/N)	SYS
WCS_SET_BAY_GRID_ITEMS_ONLY	Only update item locations that are on the grid	SYS
WCS_SPLIT_LOAD_PLAN	Automatically plan the split load orders to final destination	SYS
WCS_SPLIT_ORDER_BY_TRIP	Allow an order to be split when its items are loaded on different trips for delivery (Y/N)?	CO
WEB_SERVICE_STORE_REQ	Determines if the message request sent to the web server enquiry should be stored in the audit record - Y will store the message as a CLOB value.	SYS
WEB_SERVICE_STORE_RESP	Determines if the message in response to the web server enquiry should be stored in the audit record - Y will store the message as a CLOB value.	SYS
WEB_SERVICE_USER	User name for web service	SYS
WMS_INBOUND_ARCH	Path for WMS XML archiving	SYS
WMS_INBOUND_FAIL	Path for WMS XML failures	SYS
WMS_INBOUND_LISTING_NAME	Filename for list of files in directory for WMS XML Order Inbound	SYS
WMS_INBOUND_ORD_IDENTIFIER	Pattern for WMS Order Inbound XML	SYS
WMS_INBOUND_PATH	Path for yet to be processed XML files from WMS	SYS
WMS_LISTING_SCRIPT_NAME	Script name for WMS XML Order Inbound	SYS
WOC_MSG_SEND_COUNT	Number of message per run sent to WCS via WOC	SYS
WSA_ARCHIVE_DAYS	Determines the number of days that the web service messages will be retained in C-TMS prior to being archived.	SYS
WS_COLLECT_LOCATION	Collection location to override one provided in web service to override collection depot in partnership	CUS
WS_COL_CUTOFF	Cut-off time for web service orders from an RDC to make the next days delivery.	SYS



Parameter	Description	
WS_DERIVE_COL_WINDOW	Derive Collection windows for Web Service Orders	CO3
WS_DUMMY_DU_TYPE	Dummy DU Type used for Web Service order creation	SYS
WS_EARLY_AVAIL_TIME	Early available time for Web Service Orders	CO3
WS_MAX_MANF_RPE	Maximum RPE value for Web service	SYS
WS_NUM_OF_RETRIES_ALLOWED	Max number of times a record will be sent to a web service endpoint	SYS
WS_REASON_CODE	Default reason code for Web service	SYS
WS_USE_TRIP_STATUS	Use Trip Status for Web Service	CO3
XML_NO_DELAY_FILES	List of XML filenames that will require no delay in polling time (eg pack confirmation).	SYS
XML_OUT_SUMM_LVL	Level to summarize XML outbound message	SYS
ZERO_MANIFEST	Allow orders to be zero manifested and set to ABORTED	CO3
ZERO_PACK_REASON	Zero packed reason code	CO3
ZETES_INSTALLED	Zetes installed	SYS
ZET_INBOUND_ARCH	Path for Microlise XML archiving	SYS
ZET_INBOUND_FAIL	Path for Microlise XML failures	SYS
ZET_INBOUND_IDENTIFIER	Pattern for MIC Trip Inbound XML	SYS
ZET_INBOUND_LISTING_NAME	Filename for list of files in directory for MIC XML Trip Inbound	SYS
ZET_INBOUND_PATH	Path for yet to be processed XML files from Microlise	SYS
ZET_INC_SSCC_PREFIX	Include prefixes for SSCC formats for the Zetes interface (Y/N).	CO3
ZET_LISTING_SCRIPT_NAME	Script name foe MIC XML Trip Inbound	SYS
ZET_OUTBOUND_ARCH	Path for safe copy of XML files for Zetes	SYS
ZET_OUTBOUND_PATH	Path for yet to be collected XML files for Zetes	SYS
ZIP	Zip executable location on application server	SYS
ZIP_SERVER	Application server folder for zipped Invoice files	SYS
ZONE_POSTCODE_CHECK	Does Zone import check the postcode	SYS
zip	Location of the zip executable on the application server	SYS
API_CARRIER_PLAN	The carrier for the API process which the customer will use with pre-packed labels	CUS
DO_NOT_UPDATE_LOADING_RATES	Do not update loading rates via customer onboarding	SYS
FLEXIPOD	Set to Y to indicate the FlexiPod interface is active	SYS
FLEXIPOD_ACID	Flexipod acid	SYS
FLEXIPOD_BREAK_DROPS	Flexipod include breaks for the drops in the Add API call (Y/N)	SYS
FLEXIPOD_CARRIERS	Set to Y indicates the Carrier can control if a trip is sent to FlexiPod	SYS
FLEXIPOD_CLIENTNUM	FleXipod ClientNum sent in interface	SYS
FLEXIPOD_DEPOTS	Set to Y indicates the Depot can control if a trip is sent to FlexiPod	SYS
FLEXIPOD_DIRECT	Set to Y to indicate the FlexiPod interface is direct and not using Route Execution	SYS
FLEXIPOD_DROP	Determines the Drop level STOP-OMS or ITEM	SYS
FLEXIPOD_EXPIRY	Sets the expiry date for the manifest as a number of days after the end of the trip.	SYS
FLEXIPOD_EXTERNALSYSTEMUPDATE	Flexipod process the External System Update messages in the API call (Y/N)	SYS
FLEXIPOD_FORCEITEMSCAN	Force the items to be scanned separately: 0 to use the ScanLevel or 1 to force the scan by item.	SYS
FLEXIPOD_LISTPENDINGMANIFESTS	Flexipod process the List Pending Manifest Update messages in the API call (Y/N)	SYS
FLEXIPOD_MERGE_DROPS	Flexipod merge the orders on the drop in the Add API call (Y/N)	SYS



Parameter	Description	
FLEXIPOD_PASSWORD	Flexipod Webservice password	SYS
FLEXIPOD_PROXY	Flexipod proxy server	SYS
FLEXIPOD_READDROP	Flexipod process the Read Drop messages in the API call (Y/N)	SYS
FLEXIPOD_SCAN_LEVEL	1,2 or 3 to indicate line or item level scanning	SYS
FLEXIPOD_SCAN_TYPE	Contents and items	SYS
FLEXIPOD_SIGNATORY	Set to Y to store the SignedByName as the actual signatory as information for the order at its collection of delivery location	SYS
FLEXIPOD_SPLIT	Are orders to be split?	SYS
FLEXIPOD_SYSTEM	Flexipod SYSTEM ID sent in interface	SYS
FLEXIPOD_TPCLIENTNUM	Flexipod TPClientNum sent in interface	SYS
FLEXIPOD_USERCODE	Flexipod webservice usercode	SYS
FLEXIPOD_USERNAME	Flexipod webservice username	SYS
FLEXIPOD_WEBSERVICE	Flexipod webservice endpoint URL	SYS
FLEXIPOD_WEBSERVICE_TASK	Flexipod webservice endpoint URL for Tasks	SYS
FLEXIPOD_WEBSERVICE_UI	Flexipod webservice endpoint URL	SYS
FLEXIPOD_WEBSERVICE_UI_EXEC	Flexipod webservice endpoint URL for Route Execution	SYS
FLEXIPOD_X_API_KEY	Flexipod x-api-key for External System Update messages	SYS
IMP_DERIVE_FROM_LOCATION	Derive the collection location of an order.	COS
IMP_DERIVE_ORDER_WINDOWS	Derive the order windows.	COS
IMP_SET_ORDER_TYPE	Set the order type to RET, SLS or DIR.	COS
IMP_SPLIT_CONTACT_NAME	Split a contact name into Forename and Surname.	COS
LIMIT_ADDRESS_MATCH	Limit address matching to line1, line2 and postcode	SYS
LOOKUP_FOR_ROUTE_CODES	Display lookup button in PLANNING beside Route Code	SYS
PSD_CONTACT_ADDRESS	Polar Speed Distribution Ltd	SYS
PSD_CONTACT_TEL	Tel: +44 (0) 1525 217666	SYS
REBOOK_REQ_SUBREF	Add Rebook Sub reference when CBR exception added to item	SYS
REBOOK_SERVICE_LEVEL	Service Level For rebooked orders when set to copy use existing	SYS
RESET_MANUAL_SCHEDULE	Reset manual schedule flag from the planning screen	SYS
TMP_ENG_TRIP_PREFIX	Scheduling Engine Trip Prefix	COS
TRM_3PL_REROUTE	Reroute the order in the fixed-drop scheduling engine to the next available route for the day (Y/N)	SYS

