



EMERGENCY RELEASE - CTMS 12.0

RELNOTE ER047-078

Module	Program Name	Ver	Call/Iss	Client Ref	Pr'ty	Remarks
DATA_ADM_SYSTEM_PARAM_725398.sql	Database Script	1.1	725398	-	2	<p>Version 1.6.1.1 of DP_FLEXIPOD will be released to the 19c databases.</p> <p>Enables UpdateManifests to create and update manifests as per Route Execution.</p> <p>Refers to system parameters:</p> <ol style="list-style-type: none"> 1 .A new system parameter called FLEXIPOD_UPDATE_MANIFESTS can be set to Y to use the 'UpdateManifests' method to create manifests as per the Route Execution API. 2. A new system called FLEXIPOD_UNALLOCATED_DRIVER can be set to Y to use 'Unallocated' for the 'DriverUserCode' for the manifest in APOD when a driver has not been set for the trip. 'Unallocated' must exist as a driver in APOD. 3. The system parameter called FLEXIPOD_TPCLIENTNUM can be set for the customer, cost centre or system levels to store the client's number. Customer is the expected level. <p>PK and DL stops which are at a RDC will be excluded from APOD. Orders which are collected and delivered on the same trip will appear as separate manifests by</p>



Module	Program Name	Ver	Call/Iss	Client Ref	Pr'ty	Remarks
						drop. The planned distance should default to 0, although a distance should always exist for a trip. Also allow manifests to be updated for a drop for a customer ID that does not have a contact. Also allow the address for a manifest to be updated for a drop without special instructions. Drops can be deassigned from a manifest as an order is deassigned from a stop and a stop is deleted from a trip. DELETED trips will set the expiry date of the manifest to be in the past.
DATA_ADM_SYSTEM_PARAM_CONFIG_725398.sql	Database Script	1.1	"	"	"	"
TRG_BOOKING_REF_FLX.sql	Database Trigger	1.4	"	"	"	"
TRG_SCH_HAULAGE_FLX.sql	Database Trigger	1.4	"	"	"	"
TRG_SCH_TRIP_DRV_FLX.sql	Database Trigger	1.4	"	"	"	"
TRG_SCH_TRIP_XML_FLX.sql	Database Trigger	1.3	"	"	"	"
DP_FLEXIPOD.sql	Flexipod Package	1.6	"	"	"	"

New Parameters			
Parameter Name	Config Level	Setting Value	Result
FLEXIPOD_UNALLOCATED_DRIVER	SYSTEM	N	A driver will not be set for the manifest in APOD when a driver has not been set for the trip.
FLEXIPOD_UNALLOCATED_DRIVER	SYSTEM	Y	Uses 'Unallocated' for the 'DriverUserCode' for the manifest in APOD when a driver has not been set for the trip. 'Unallocated' must exist as a driver in APOD.
FLEXIPOD_UPDATE_MANIFESTS	SYSTEM	N	Uses the 'Add' method to create the manifests as per the public API.
FLEXIPOD_UPDATE_MANIFESTS	SYSTEM	Y	Uses the 'UpdateManifests' method to create the manifests as per the Route Execution API.
FLEXIPOD_TPCLIENTNUM	SYSTEM	Populated	Stores the 'TPClientNum' for the system.
FLEXIPOD_TPCLIENTNUM	COST_CENTRE	Populated	Stores the 'TPClientNum' for the cost centre.
FLEXIPOD_TPCLIENTNUM	CUSTOMER	Populated	Stores the 'TPClientNum' for the customer. This is the expected level.

